



Specifications

Band Circumference	4.75 to 12.25 in. (121 to 311 mm)
Link Width	0.25 in. (6 mm)

Item	Description
09080	Wristband Only
09081	Wristband with 6' Coil Cord
09082	Wristband with 12' Coil Cord

Features and Components

- A. ABS cap with slotted opening for size adjustment
- B. 300 series stainless steel back plate
- C. 4 mm snap stud machined from 300 series stainless steel. Fits to 4 mm spring loaded socket. Coil cord disengages from snap with 1-5 lbs. of perpendicular force.
- D. Inside links constructed of 300 series stainless steel
- E. Link exterior is covered with a .002" polyphenylsulfone insulated cap. Provides greater than 5,000 volts RMS insulation per ASTM D149.
- F. Size is adjusted by sliding 1 to 6 links on each side of the buckle
- G. Underwriters Laboratories listing 90P1C

Meets required limits of ANSI/ESD S20.20 and requirements of ANSI/ESD S1.1

All tolerances are ±10% unless otherwise specified

ULTRA LIGHT METAL EXPANSION WRISTBAND



5 Commonwealth Ave
Woburn, MA 01801
Phone 781-665-1400
Toll Free 1-800-517-8431

[Visit us at www.TestEquipmentDepot.com](http://www.TestEquipmentDepot.com)

DRAWING NUMBER
09080

DATE
September 2018