



**Specifications**

Band Circumference	4.75 to 12.25 in. (121 to 311 mm)
Link Width	0.25 in. (6 mm)

Item	Description
<a href="#">09080</a>	Wristband Only
<a href="#">09081</a>	Wristband with 6' Coil Cord
<a href="#">09082</a>	Wristband with 12' Coil Cord

**Features and Components**

- A. ABS cap with slotted opening for size adjustment
- B. 300 series stainless steel back plate
- C. 4 mm snap stud machined from 300 series stainless steel. Fits to 4 mm spring loaded socket. Coil cord disengages from snap with 1-5 lbs. of perpendicular force.
- D. Inside links constructed of 300 series stainless steel
- E. Link exterior is covered with a .002" polyphenylsulfone insulated cap. Provides greater than 5,000 volts RMS insulation per ASTM D149.
- F. Size is adjusted by sliding 1 to 6 links on each side of the buckle
- G. Underwriters Laboratories listing 90P1C

Meets required limits of ANSI/ESD S20.20 and requirements of ANSI/ESD S1.1

All tolerances are ±10% unless otherwise specified

**ULTRA LIGHT METAL EXPANSION WRISTBAND**



5 Commonwealth Ave  
Woburn, MA 01801  
Phone 781-665-1400  
Toll Free 1-800-517-8431



**DRAWING NUMBER**  
09080

**DATE**  
September 2018