



- A. Fixed light gray ABS cap with slotted opening to allow size adjustment.
- B. 300 series stainless steel backplate forms channel to hold up to 10 links of band allowing size adjustment.
- C. Machined nickel plated steel stud. Fits Desco's MagSnap® coil cords. Coil cord disengages from from snap with 1-5 lbs. of perpendicular force.
- D. Metal expansion wrist strap. Inside links are constructed of 300 series stainless steel. Width of links is 0.630". Minimum Circumference: 5.75" and Maximum Circumference: 13".

- E. 0.002" polyphenylsulfone sheet is laminated to each link. Provides >5,000 volt RMS insulation per ASTM D149. Scratch resistant. Color white.
- F. Size is adjusted by sliding 1 to 10 links of the band into the backplate "C" channel.
- G. 300 series stainless steel clip for electrical contact between stud and backplate.
- H. Underwriters Laboratory listing 90P1C.

Meets ANSI/ESD S20.20 and Wrist Strap standard ANSI/ESD S1.1.

Standard items that include MagSnap® Metal Expansion Wristbands

Item	Description	Cord Style	Accessories
09210	Wristband	N/A	None
09211	Wrist Strap	6 Foot Magsnap® Coil Cord	Alligator Clip
09212	Wrist Strap	10 Foot Magsnap® Coil Cord	Alligator Clip

Unless otherwise noted, tolerance ± 10%



Made in the United States of America

Meets ANSI/ESD S20.20 wristband resistance interior < 100 kilohms (< 1 x 10⁵ ohms) per ANSI/ESD S1.1.
Meets ANSI/ESD S20.20 wristband resistance exterior >10 megohms (> 1 x 10⁷ ohms) per ANSI/ESD S1.1.

JEWEL MAGSNAP® WHITE METAL ADJUSTABLE WRIST STRAPS



DRAWING NUMBER
09210

DATE:
September
2014