AUTO

106

## Core temperature thermometer

testo 106 - The compact food thermometer

Ideal for use in the food sector

TopSafe: dishwasher-safe protective cover (IP67), protects from dirt and impact

Small, handy and always ready to hand

Audible and optical alarm

Automatic final value recognition (Auto-hold)

Hardly visible punctures

Certified according to EN 13485 (only in combination with TopSafe)



The core thermometer testo 106 is especially fast and robust. Its small handy shape means it is always close to hand and ready for use. Thanks to its very thin and robust measurement tip, it is excellently suited to core temperature checks in gastronomy, hotels, large kitchens, supermarkets etc. The dishwasher-safe TopSafe protects the instrument from dirt, water and impact. The testo 106 is comform to HACCP as well as EN 13485. If required, upper and lower limit values can be stored in the instrument; as soon as these values are violated, audible and optical warning signals are given. This alarm function and the automatic final value recognition facilitate measurement and support you in recognizing and interpreting measurement values quickly and correctly.



99 Washington Street Melrose, MA 02176 Phone 781-665-1400 Toll Free 1-800-517-8431

## Technical data / Accessories

|   | Sensor type   | NTC  |
|---|---|--|
| esto 106  | Measuring range                                       | -50 to +275 °C   |
| sto 106, food core thermometer incl. probe otecting cap, battery and calibration protocol   | Accuracy<br>±1 digit                                  | ±1 % of m.v. (+100 to +275 °C)<br>±0.5 °C (-30 to +99.9 °C)<br>±1 °C (-50 to -30.1 °C) |
| noted ting dup, buttery and canoration protocol   | Resolution  | 0.1 °C   |
|   | General technical data                                |  |
| art no. 0560 1063   | Storage temperature                                   | -40 to +70 °C  |
|   | Operating temperature                                 | -20 to +50 °C  |
|   | t <sub>99</sub>                                       | 10 s   |
|   | Battery type  | 3V button cell (CR 2032)   |
|   | Battery life  | 350 h  |
|   | Weight  | 80 g   |
| et testo 106  | Dimensions<br>Length Probe shaft /<br>Probe shaft tip | 215 x 34 x 19 mm<br>55 mm / 15 mm  |
| et testo 106, food core thermometer incl.<br>pSafe (waterproof protection case, IP67,<br>tachment clip, probe protection cap, battery | Diameter Probe shaft<br>/ Probe shaft tip             | Ø 3 mm / Ø 2.2 mm  |
| d calibration protocol  | Display   | LCD, 1 line  |
| no. 0563 1063   | Housing material                                      | ABS  |
|   | Protection class                                      | IP 67 with TopSafe   |

## Accessories

| Accessories for measuring instrument  |           |  |
|---|-----------|--|
| TopSafe (indestructible protection case); waterproof and dishwasher-safe protection case (IP67)         | 0516 8265 |  |
| Holding clip with probe protection cap  | 0554 0825 |  |
| ISO calibration certificate/temperature ; for air/immersion probes, calibration point +60°C             | 0520 0063 |  |
| ISO calibration certificate/temperature ; for air/immersion probes, calibration point -18°C             | 0520 0061 |  |
| ISO calibration certificate/temperature ; for air/immersion probes, calibration point 0°C               | 0520 0062 |  |
| ISO calibration certificate/temperature ; for air/immersion probes, calibration points -18°C; 0°C       | 0520 0041 |  |
| ISO calibration certificate/temperature ; for air/immersion probes, calibration points -8°C; 0°C; +40°C | 0520 0181 |  |

Warranty

Standard

2 years EN 13485

Part no.

Test Equipment Depot - 800.517.8431 99 Washington Street, Melrose, MA 02176 TestEquipmentDepot.com 0981 9494/msp/A/01.2017