

# 9" Ergo Crimp

Higher Performance  
Superior Comfort  
Reliability



**The next generation** of crimp tool technology designed around the user. Crimping is even easier and more comfortable. The “straight plate” lower jaw assembly eliminates critical structural stress points, common in most competitive tools - it will not break under heavy stress and will last for years to come. Higher performance, reliability and comfort, it's all here.

- Reduced handle grip distance makes it ideal for all hand sizes and allows for prolonged, comfortable use
- Smooth triple ratchet design eliminates breakover hand force
- Adjustable cam allows precision ratchet adjustment for a perfect crimp, no matter the die set or application
- Accepts crimp die sets from most other popular tools. Your old crimping dies will work!
- Built-in safety release

## Technical Data

- Length: 9" (229mm)
- Weight: 16oz (454g)

## Ordering Information

Description	P/N	UPC CODE
9" Ergo Crimp Tool, Frame Only	16500C	849160006664

See Die Sets  
and More



***We Make Connections EZ!***

©2014 Platinum Tools, Inc. All rights reserved. 9" Ergo Crimp Tool PF TS 3/14

**Test Equipment  
Depot**  
  
1-800-517-8431

99 Washington Street  
Melrose, MA 02176  
Phone 781-665-1400  
Toll Free 1-800-517-8431



Visit us at [www.TestEquipmentDepot.com](http://www.TestEquipmentDepot.com)

# 9" Ergo Crimp Tool Dies and Applications



Die	Crimp	Part # Tool & Die / Die Only	Cable Types	Crimp Type/Sizes	Connector Types
		<b>16501C / 17051C</b>	22-10 AWG Solid or Stranded	3 Cavity 22-18 AWG (.34-.75 mm <sup>2</sup> ) 16-14 AWG (1.5-2.5 mm <sup>2</sup> ) 12-10 AWG (4-6 mm <sup>2</sup> )	Heavy Duty Insulated Terminals and Lugs
		<b>16502C / 17052C</b>	22-8 AWG Solid or Stranded	4 Cavity 22-18 AWG (.34-.75 mm <sup>2</sup> ) 16-14 AWG (1.5-2.5 mm <sup>2</sup> ) 12-10 AWG (4-6 mm <sup>2</sup> ) 8 AWG (10 mm <sup>2</sup> )	Non-Insulated Terminals
		<b>16503C / 17053C</b>	RG-59/6 Belden 8281/1694A	Hex .042 / .068 / .255 / .324	BNC, TNC, HDTV
		<b>16504C / 17054C</b>	RG-58, RG-59, RG-62	Hex .068 / .213 / .255	BNC, TNC 3 Piece
		<b>16505C / 17055C</b>	RG-59, RG-6	Hex .256 / .315 / .346	F Type, 1 & 2 Piece CATV
		<b>16506C / 17056C</b>	RG-6, RG-6 Quad 8281, 1694A, 1695 1505, 9259, 9231	Hex .360 / .324 / .068	BNC, TNC, F Type
		<b>16507C / 17057C</b>	22-10 AWG Solid or Stranded	3 Cavity 22-18 AWG (.34-.75 mm <sup>2</sup> ) 16-14 AWG (2.5-1.5 mm <sup>2</sup> ) 12-10 AWG (4-6 mm <sup>2</sup> )	Standard Duty Commercial Insulated Terminals & Lugs
		<b>16508C / 17058C</b>	22-10 AWG Stranded	3 Cavity 22-18 AWG (.34-.75 mm <sup>2</sup> ) 16-14 AWG (2.5-1.5 mm <sup>2</sup> ) 12-10 AWG (4-6 mm <sup>2</sup> )	Commercial Pin & Socket Type Contacts, Open Barrel Contacts, Box Contacts
		<b>16509C / 17059C</b>	RG-174, 187, 188, 316 Mini Coaxial	Hex .178 / .128 / .068	SMA, SMB, Mini 59, BNC, TNC, Mini UHF
		<b>16510C / 17060C</b>	RG-8, RG-11, RG-213, RG-214, LMR400	Hex .429 / .100 / .080	N Type Plugs
		<b>16511C / 17061C</b>	RG-59/62, 734, 735, RG-6	Hex .311 / .256 / .200 / .068 / .039	HDTV, True 75 Ohm BNC, TNC



**Contact us about custom dies.**

Description	P/N	UPC CODE
Quick Change Die Screws, Set of 2	17099C	849160000617

