



Band Size	Circumference	
	Min.	Max.
Small	5.5" (140mm)	9" (229mm)
Medium	6" (152mm)	11" (279mm)
Large	7" (178mm)	12" (305mm)

Item	Band Size	Coil Cord
<a href="#">19886</a>	Small	Not Included
<a href="#">19887</a>	Medium	Not Included
<a href="#">19888</a>	Large	Not Included
<a href="#">19889</a>	Small	6' ( <a href="#">19880</a> )
<a href="#">19890</a>	Medium	6' ( <a href="#">19880</a> )
<a href="#">19891</a>	Large	6' ( <a href="#">19880</a> )
<a href="#">19892</a>	Small	12' ( <a href="#">19881</a> )
<a href="#">19893</a>	Medium	12' ( <a href="#">19881</a> )
<a href="#">19894</a>	Large	12' ( <a href="#">19881</a> )

- A. .002" polyphenylsulfone sheet laminated to each link. Provides >5,000 Volt RMS insulation per ASTM D149. Will not flake or peel.
- B. Unique dual contact design is to be paired with a [Desco MagSnap™ 360 Coil Cord](#) (not included) for a superior electrical connection. The magnetic connection made with the coil cord maintains a 1-5 pound perpendicular breakaway force to prevent accidental disconnects.
- C. Black ABS plastic cap. Molded with "MagSnap 360" trademark.
- D. Underwriters Laboratory Listing 90P1C.
- E. Inside links are constructed of 300 Series Stainless Steel. Width of links is 0.63".
- F. Black ABS plastic insulator separates band into halves.

Meets required limits of ANSI/ESD S20.20 and requirements of ANSI/ESD S1.1.

*All tolerances are 10% unless otherwise specified. Specifications and procedures are subject to change without notice.*



U.S. Patent Pending

## MAGSNAP 360™ DUAL-WIRE METAL EXPANSION WRISTBAND

# DESCO

**DRAWING NUMBER**  
19886

**DATE**  
May  
2014