



epot - 800.517.8431 - 99 Washington Street Melrose, MA 02176 TestEquipmentDepot.com

> The 2300 Series Dual Conductor Coil Cord is for use with dual conductor wrist straps and SCS Workstation Monitors. The Dual Conductor Coil Cord features an improved grip that is wider in diameter and easier to grasp when inserting and removing the cord from the remote unit. 1 megohm current limiting resistors on both conductors that meet the resistance requirements of ANSI/ESD S20.20, EIA 625.

Properties	Typical Value
Resistance	One megohm
Flex Life	> 16,000 flexes
Plug Size	3.4mm
Plug Type	Straight or Right Angle
Color	Gray

Item	Description	
<u>2360</u>	5ft. (1.5m), Straight	
<u>2370</u>	10ft. (30.m), Straight	
<u>2371</u>	20ft. (6.1m), Straight	
2360R*	5ft. (1.5m), Right Angle	
2370R*	10ft. (30.m), Right Angle	
2371R*	20ft. (6.1m), Right Angle	

<sup>\*</sup>To be used with SCS Dual Wire Monitors only

	Test Equipment De
Straight	
	Section of the sectio
Right Angle	

Note: This product is not recommended for use on equipment with operating voltage exceeding 250 VAC.

Specifications and procedures subject to change without notice.



2300 SERIES - DUAL CONDUCTOR COIL CORD

DRAWING DATE NUMBER 2300 Series

February 2017