

# **Mighty Cam ES**

## Digital Microscope

[22x - 147x] on Post Stand w/ Gooseneck LEDs and 3D Viewer

Digital Inspection and Measurement System featuring our Detented Micro Lens with a 3D Viewer, Mighty Cam ES Camera mounted on post stand with flexible gooseneck LEDs, and includes a 22 inch HD LED Monitor. **Provides a magnification range of 22x to 147x.** 



### **Features**

- 3D Viewer allows users to inspect from all angles by simply rotating the viewer
- Micro zoom lens with four detented zoom settings (ideal for accurate and repeatable measurements)
- Mighty Cam ES camera provides excellent image quality in HDMI or USB modes (measurement software included)
- Post stand with adjustable LEDs on flexible goosenecks (LEDs can be positioned where needed for optimal illumination)
- 22" HD Monitor included
- \*3D viewer is required to be in the off position to perform measurements

Inspect from Any Angle

No need to move

the part

Micro Zoom Lens 22x - 147x Magnification (22" Monitor) Mighty Cam ES


HDMI/USB Camera designed for quick & accurate inspection Gooseneck
LEDs
Position LEDs
for optimal

illumination



#### **HDMI** Mode

(Inspect in real-time, capture images, and more without a PC)



### **Inspect Parts from Any Angle**

Mighty Cam ES		
22x-147x on Post Stand w/ Gooseneck LEDs & 3D Viewer		
Item #	26700-151-C05-259-570	
Magnification	3D Viewer ON 22x - 147x (22" Monitor)	<b>3D Viewer OFF</b> 22x - 147x (22" Monitor)
Working Distance	<b>3D Viewer ON</b> 0.91" (23mm)	3D Viewer OFF 3" (76.2mm)
Resolution	<b>Via USB 2.0</b> 1920 x 1080 @ 15FPS	<b>Via HDMI</b> 1920 x 1080 @ 15FPS
Software	Built-in Software Cloud 1.0 ver	PC Software ISCapture
Interface	USB 2.0 & HDMI	
Package Contents	26100-259: Mighty Cam ES     26700-170: 3D Viewer     26700-151-C05: Micro Lens + 0.5x Coupler     16700-151 AP: Lens Adapter Plate     26800B-570: Heavy Duty Post Stand     26800B-517: Focus Mount     26200B-224: Flexible Gooseneck LEDs for Post Stands     26700-406: 22" HDMI LCD Monitor	