Test Equipment Depot - 800.517.8431 - 99 Washington Street Melrose, MA 02176



TestEquipmentDepot.com



This SCS Dual-Wire Thermoplastic Wrist Strap consists of an insulative exterior with a conductive interior and a 3.4mm dual conductor jack. The wrist strap is light weight, low profile and safely makes contact with human skin. The "zipper" style latching mechanism easily adjusts to most wrist sizes. Made to be used in conjunction with all SCS Workstation Monitors. Meets requirements of ANSI/ESD S20.20 and Wrist Strap standard ANSI/ESD S1.1, and meets EN 61340-5-1 and IEC 61340-4-6. Designed for use with SCS Dual-Wire Coil Cords (not included).

Specifications	Typical Value	
Material	Thermoplastic elastomer; copolyester	
Color	Blue	
Plug Size	3.4mm	
Cord Removal Force	1 to < 5 lbs.	
Size	Adjustable, 1.7 to 2.6in. diameter	
Resistance Inside	< 1 x 10 ⁵ ohms	
Resistance Outside	> 1 x 10 ⁷ ohms	
Cleanable	Water/mild detergent or 10% isoproyl solution	

Item	Description
<u>4720</u>	Dual-Wire Thermoplastic Wrist Strap

U.S. Patent 6,256,847

Unless otherwise noted, tolerance ±10%

Specifications and procedures subject to change without notice.



DUAL-WIRE THERMOPLASTIC WRIST STRAP

DRAWING	DATE
NUMBER	May
4720	2017

© 2017 DESCO INDUSTR ES NC. Employee Owned