



Mastercool[®] Inc.
"World Class Quality"

**Test Equipment
Depot**
1-800-517-8431

99 Washington Street
Melrose, MA 02176
Phone 781-665-1400
Toll Free 1-800-517-8431

Visit us at www.TestEquipmentDepot.com

52224-D **MULTI-LASER INFRARED
THERMOMETER**



- Distance:Spot: 12:1
(90% energy covered)
- Measurement Range: -60 to 760°C
(-76 to 1400°F)
- Operating Range: 0~50°C (32~122°F)
- Accuracy, (Tobj=15-35°C, Tamb=25°C):
+/-1.0°C (1.8°F)
- Accuracy (Tamb=23 +/- 3°C): 0~550°C:
+/-2% of reading or 2°C (4°F) whichever
is greater -60~0°C: +/- (2°C+0.05/
degree)
- Emissivity: 0.95 default - adjustable 0.1
to 1 step .01
- Resolution: 0.1°C/0.1°F at -76 to
999.9(°C/°F), otherwise 1°C/1°F
- E, MAX, MIN, DIF and AVG modes
- Response Time (90%): 1sec
- Battery Life: Typ.12, min 9 hours
continuous use (Alkaline, with Laser and
Back Light.)
- Dimensions: 119.2 x 47.5 x 171.8 mm
(4.7 x 1.87 x 6.76")
- Weight: 255.7 g (9.02 oz) including
batteries (AAA - 2pcs)

The multi-laser infrared thermometer safely monitor hot, hazardous, or hard to reach materials without contamination or damage to the surface. Simply point at target, pull the trigger, and read the temperature on the large, backlit LCD display.

Applications:

- Pinpointing radiator core restrictions
- Measuring exhaust and emission control (catalytic converter) temperatures to detect problems
- Diagnosing combustion problems by measuring exhaust manifold temperatures
- Pinpointing air conditioning system restrictions
- Measuring tire temperatures
- Measuring drum, rotor, and bearing temperature
- Measuring the racetrack temperature

