



Humidity/temperature measuring instrument

testo 625 – Digital thermohygrometer with App connection


Simple, fast and precise measurement of air temperature and relative humidity

Calculation of dewpoint and wet bulb temperature

Fast in-app configuration, graph history, second screen and measurement data memory in the testo Smart App

Audible alarm sounds if a limit value is exceeded

Timed and point mean value calculation



Relative humidity and air temperature are two decisive factors for the assessment of **indoor air quality and comfort**. So if you want to ensure that people are comfortable indoors or that optimum conditions prevail in **storage rooms**, the compact testo 625 thermohygrometer is the ideal choice.

To obtain precise results as quickly and easily as possible, the testo 625 not only calculates dewpoint and wet bulb temperature automatically, but the time and the point averages are also displayed immediately.

And with the testo Smart App, you get the most out of the thermohygrometer:

- Configure measuring instrument
- Display graphical measured value curve
- Save measurement data
- Manage customers and measuring points
- Documentation on site
- E-mail dispatch of the report
- Second screen display with the testo Smart App




Ordering data / technical data / accessories

testo 625

testo 625, humidity/temperature measuring instrument with App connection and audible alarm, incl. transport bag, calibration protocol and 3 x AA batteries

Order no. 0563 1625



The testo Smart App

- Simple and fast: Measurement menus for numerous applications provide optimum support in configuring and carrying out the measurement
- Clear graphical presentation of readings, e.g. as a table, for quick interpretation of results
- Create digital measurement reports including photos as PDF/CSV files on site and send via e-mail



Free download
for Android and iOS



Sensor types

Testo humidity sensor, capacitive

Measuring range	0 to 100 %RH
Accuracy ± 1 digit	2.5 %RH (5 to 95 %RH)
Resolution	0.1 %RH

NTC

Measuring range	- 4 to 140 °F
Accuracy ± 1 digit	± 0.9 °F
Solution	0.1 °F

General technical data

Operating temperature	Measuring instrument: -4° to 122 °F Probe: -4° to 158 °F
Storage temperature	-4° to 122 °F
Battery type	3 x AA
Battery life	100 h
Dimensions	Measuring instrument: 8.2 x 2.4 x 1.1 in Probe: 0.47 x 0.59 in
Weight	0.44 lbs
Protection class	Measuring instrument: IP40 / probe: IP20
Housing material	ABS + PC / TPE

Accessories

Accessories	Order no.
testo Bluetooth® printer, incl. 1 roll of thermal paper, rech. battery and power supply	0554 0621
Spare thermal paper for printer (6 rolls), measurement data documentation can be read for up to 10 years	0554 0568
NIST RH Certificate at 2 Std Pts (11.3% and 75.3%RH)	0520 0006
NIST RH Certificate at 3 Std Pts (11.3%, 50%, 75.3%)	0520 0013
NIST RH Certificate at 3 custom points (between 10% and 90% RH)	0520 0083