

RIDGID®

SeeSnake® NANOREEL® Inspection Camera



The RIDGID® SeeSnake® NANOREEL® opens up new possibilities in drain inspection with the smallest-diameter camera and most flexible push cable of all SeeSnake® systems. Inspect a wide array of specialty applications that previously only bore scopes could reach.

- Small 15.5 mm camera head with ultra flexible push cable navigates tight spaces in 1" to 2.5" lines
- A built-in kickstand offers in-field versatility with multiple configurations
- Lightweight and compact carrying case design is easy to carry to jobsites and store in-between
- Integrated 512 Hz sonde allows for easy line tracing and locating



SPECIFICATIONS

- Camera
 - Diameter..... 15.5 mm
 - Type..... Fixed
- Line Capacity 1" to 2 1/2"
(25 mm to 64 mm)
- Push Cable
 - Length 82' (25 m)
 - Diameter..... 0.28" (7.2 mm)
 - Minimum Bend Radius..... 1.5" (38 mm)
- Cable Flexibility..... Ultra Flex
- Sonde..... 512 Hz, Integrated
- Weight..... 12.1 lb. (5.5 kg)
- Length..... 13.3" (337 mm)
- Width..... 8.8" (224 mm)
- Height..... 16.2" (411 mm)
- Drum Diameter 12" (305 mm)

ORDER INFORMATION

| CATALOG NO. | DESCRIPTION | WEIGHT | |
|-------------|--------------------|--------|------|
| | | (lb.) | (kg) |
| 70038 | SeeSnake® NANOreel | 12.1 | 5.5 |



ACCESSORIES

| CATALOG NO. | DESCRIPTION |
|-------------|---|
| 42778 | 30 mm and 25 mm Pipe Guide Set, 15 mm Camera, Pkg of 2 |
| 70723 | Kit, Slipping Connector w/3m Cable |
| 70718 | Kit, CA-350 Adapter, Slipping Connector w/3m Interconnect Cable |
| 67808 | Kit, CA-350 Adapter w/Docking Handle |
| 55898 | micro CA-350 Inspection Camera |
| 69758 | Kickstand Accessory |
| 71498 | Spare, Slipping Connector |
| 67307 | Interconnect Cable, 3m |

