

RIDGID

SeeSnake® microREEL® CA Inspection Camera



Optimize your inspections with the RIDGID® SeeSnake® microREEL® CA designed with a lightweight, compact profile and camera docking handle for easy portability. The mid-flex push cable and 25 mm camera head can easily navigate turns and inspect up to 100 ft.

- Equipped with a CA-350 adapter and docking handle to easily be used with a micro CA-350 inspection camera*
- A built-in kickstand offers in-field versatility with multiple configurations
- Integrated 512 Hz sonde allows for easy line tracing and locating
- Multiple monitor compatibility allows you to use the micro CA-350 inspection camera or any SeeSnake monitor

*micro CA-350 inspection camera sold separately



RIDGID.COM/seesnake

SPECIFICATIONS

- Camera
 - Diameter..... 25 mm
 - Type..... Fixed
- Line Capacity 1 1/2" – 4"
(38 mm to 101 mm)
- Push Cable
 - Length 100' (30 m)
 - Diameter..... 0.27" (6.7 mm)
 - Minimum Bend Radius..... 2.5" (64 mm)
- Cable Flexibility..... Mid Flex
- Sonde..... 512 Hz, Integrated
- Weight..... 12.7 lb. (5.8 kg)
- Length..... 13.3" (337 mm)
- Width..... 8.8" (224 mm)
- Height..... 16.2" (411 mm)
- Drum Diameter..... 12" (305 mm)

ORDER INFORMATION

CATALOG NO.	DESCRIPTION	WEIGHT	
		(lb.)	(kg)
70803	SeeSnake microREEL CA	12.7	5.8

ACCESSORIES

CATALOG NO.	DESCRIPTION
35338	45 mm Pipe Guide, 25 mm Camera, Pkg 2
40598	60 mm Pipe Guide, 25 mm Camera, Pkg 2
17553	Spanner wrench, 25 mm
70723	Kit, Slipring Connector w/3m Cable
70718	Kit, CA-350 Adapter, Slipring Connector w/3m Interconnect Cable
67808	Kit, CA-350 Adapter w/Docking Handle
55898	micro CA-350 Inspection Camera
69758	Kickstand Accessory
71498	Spare, Slipring Connector
67307	Interconnect Cable, 3m



Scan for more information on HQx Live

