5 inch tester with HDMI out (1080P)

Features:

- All-in-one CCTV Tester
- 5-inch IPS touch screen, 1920x1080 resolutions
- 8MP CVI/ TVI/ AHD camera test
- H.265/H.264, 4K video display via mainstream
- HDMI output, support1080P
- DC12V 3A, 48V PoE power output
- Rapid ONVIF, Create the test report and modify IP address, etc.
- Auto HD, auto recognize HD coax camera type and resolution
- RJ45 TDR cable test, cable quality test
- UTP cable test, detect open, shorts, mis-wiring
- Works 4 hours after a 2~3 hour charge
- Includes 7.4V Li-ion battery, AC adapter/charger, DC power cable, BNC cable, RS485 cable, audio cable, wrist strap, and carrying case



Specifications

IPC Protocol	ONVIF, RTSP, RTP
Network Test	10/100/100M detect; IP address scan, ping, packet test,
	DHCP server;trace route; link monitor
Rapid IP Discovery	Discover the IP address in the connected device's network segment
WiFi	Display upload/download connection speeds: create a Wifi hotspot
IP Camera Test	Display image from the 4K H.265 camera by mainstream
Data Monitor	Capture and analyze the command data from controlling device; can
	also send hexadecimal
Video Test	NTSC/PAL/HD-CVI 3.0/AHD 3.0/HD-TVI 3.0
Audio Test	1 channel audio signal input
PTZ Control Test	Support RS485; Compatible with more than 30 protocols
Lens Simulation	Simulate different lens display areas: 2.8, 3.6, 4, 6, 8, 12, 16, 25mm
POE Test Power	48V power output; Max power 24W
12V Power Output	12V/3A output interface
Snapshot/Video	Capture and record images and live video with playback
Memory	Internal: 3.2GB; External: optional microSD 32GB max
Display	5" IPS Touch, 1920 x 1080
Power	Lithium-ion battery 5 hour work time
Dimensions	183 x 110 x 36.5mm

Ordering Information:

8150 CamView5 Security Camera Tester



5 Commonwealth Ave Woburn, MA 01801 Phone 781-665-1400 Toll Free 1-800-517-8431

Visit us at www.TestEquipmentDepot.com

