


## R1234yf 1/2" ACME-LH THREAD PIERCING DESIGN CAN TAP VALVE

### FEATURES

- 1/2" ACME-LH thread for use with R1234yf pierce designed cans
- Exclusive "full grip" valve knob
- All metal construction provides durability
- Gasket assures leak proof operation
- Built-in safety check
- Meets SAE J2844



### SAFETY WARNING AND PRECAUTIONS



**WARNING:** Before removing valve from can for disposal, make sure all refrigerant has been used.

**WARNING:** Wear safety glasses

### OPERATING INSTRUCTIONS

1. Connect can tap fitting to hose and coupler assembly (not included).
2. Connect refrigerant can to the bottom of can tap, turn *counterclockwise*.
3. Turn handle clockwise to pierce the refrigerant can.
4. Turn *counterclockwise* to flow refrigerant.
5. First time use, purge air in hose.
6. Connect coupler (not included) to low side of system, refrigerant will flow into the system.
7. When can is empty properly discard can.



99 Washington Street  
Melrose, MA 02176  
Phone 781-665-1400  
Toll Free 1-800-517-8431



Visit us at [www.TestEquipmentDepot.com](http://www.TestEquipmentDepot.com)

⚠ **WARNING:** This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).