Digital Rockwell Hardness Tester

Touch Screen Functions w/One Touch Testing Feature!

Direct Loading Method With Load-Cell Instead Of Dead Weight System. High Speed Test Cycle and Extremely Accurate Loading Control

- Automatic conversions to HB, HV, Regular Rockwell Scales
- Touch Screen selectable system
- Upper/Lower Limit Settings

	1
Minor Load	10 Kgf
Major Load	60 Kgf, 100 Kgf, 150 KGF
Test Force Application	Load Cell Closed Loop
Test Force Control	Motorized
Results Display	Hi Def LCD Digital Readout
Resolution	0.01HR
Vertical Capacity	7.80″
Throat Depth	5.90″
Height	700mm
Width	600mm
Depth	250
Weight	220 lbs
	"VIA

Options: NIST/ASTM certified test blocks, penetrators and kits are available. Please refer to pages 48-52. PLEASE CONTACT US FOR DETAILS. Accessories Included: C-scale Diamond Indenter 1/16" Ball Indenter 3- HRC test Blocks 1- HRB Test Block 1-HRA Test Block Test Table 5.87" (150mm) Flat Anvil 2.5" (63mm) Std. V- Anvil Dust Cover Accessory Case

Load Cell, Closed Loop, Superficial Rockwell Hardness Tester!

900-367

phase II

This digital Rockwell hardness tester with fully automated load/unload procedures affords highly sensitive and accurate readings. Micro computer controlled Touch Screen with USB output to PC. The 900-367 digital Rockwell hardness tester offers programmable scale conversions, dwell times, statistical capabilities and test counter. Capable of testing in all of the regular Rockwell hardness scales.

Test resolution: 0.01HR Rockwell unit;
Operation temperature: 50° - 95°F (10°C~35°C)

- Ambient environment: clean, no vibration, no strong magnetic field, and no corrosive medium
- Power supply: single phase, AC, 110-220 with manual change, 50~60Hz, 4A;
- Machine dimension: 700mm×250mm×600mm.

Test Equipment Depot 1-800-517-8431

99 Washington Street Melrose, MA 02176 Phone 781-665-1400 Toll Free 1-800-517-8431

/isit us at www.TestEquipmentDepot.com