

Cast Iron Body! w/Touch Screen Functions

	Minor Load	10 Kgf
	Major Load	60 Kgf, 100 Kgf, 150 KGF
_	Test Force Application	Load Cell Closed Loop
	Test Force Control	Motorized
	Results Display	Hi Def LCD Digital Readout
\	Resolution	0.01HR
	Vertical Capacity	8.0"
Ì	Throat Depth	7.8"
/	Height	22"
	Width	8"
1	Depth	31"
	Weight	175 lbs

Test Equipment
Depot
1-800-517-8431

Options:

NIST/ASTM certified test blocks, penetrators and kits are available.

Please refer to pages 48-52.

PLEASE CONTACT US

FOR DETAILS.

Accessories Included:

C-scale Diamond Indenter 1/16" Ball Indenter

3- HRC test Blocks

1- HRB Test Block

1-HRA Test Block

Test Table 5.87" (150mm)

Flat Anvil 2.5" (63mm)

Std. V- Anvil

Dust Cover

Accessory Case

- Test resolution: 0.01HR Rockwell unit;
- Operation temperature: 50° 95°F (10°C~35°C)
- Ambient environment: clean, no vibration, no strong magnetic field, and no corrosive medium
- Power supply: single phase, AC, 110-220 with manual change, 50~60Hz, 4A;

Direct Loading Method With Load-Cell Instead Of Dead Weight System. High Speed Test Cycle and Extremely Accurate Loading Control

- Automatic conversions to HB, HV, Regular Rockwell Scales
- Touch Screen selectable system
- Upper/Lower Limit Settings

Load Cell, Closed Loop, Superficial Rockwell Hardness Tester!

900-415

This digital Rockwell hardness tester with fully automated load/unload procedures affords highly sensitive and accurate readings. Micro computer controlled Touch Screen with USB output to flash drive. The 900-415 digital Rockwell hardness tester offers programmable scale conversions, dwell times, statistical capabilities and test counter. Capable of testing in all of the regular Rockwell hardness scales.