99 Washington Street Melrose, MA 02176 Phone 781-665-1400 Toll Free 1-800-517-8431



Visit us at www.TestEquipmentDepot.com

18 VOLT CORDLESS, 1.5 CFM, 2 STAGE VACUUM PUMP



SPECIFICATIONS:

- . No. of Stages: 2
- Free Air Displacement: 1.5 CFM (42-35 I/min at 60-50 Hz)
- Motor: DC 18V, 90 W
- Ultimate Vacuum: 15 microns/3 Pa
- Oil Capacity: 3.5 oz. (105 ml)
- Dimensions without battery: 9.9 x 3.7 x 6.1" (252 x 94 x 155 cm)
- Net Weight: 7.9 lb (3,6 kg)

Rechargeable Battery

• Li-ion 18 V 5.0 Ah

Battery Charger

- Input 100-240 V, 50-60 Hz, 73 W
- Output: 18V/14.4V 3A

90058-5A

Complete kit includes: 18 V cordless vacuum pump, 1/4" SAE port, Mastercool designed rechargeable battery, Mastercool adapter sleeve and standard 110/220V battery charger

All vacuum pump complete kits are available with the following battery charger cable, please add:

-E for 220V schuko / -AUS for 220V Australia / -BR for 220V Brazil

18 V cordless vacuum pump, 1/4" SAE port (without battery and adapter sleeve)

90058-AUT-5A

Complete kit includes: 18 V cordless vacuum pump, 1/4" SAE port and 1/2" ACME adapter, Mastercool designed rechargeable battery, Mastercool adapter sleeve and standard 110V battery charger

90058-A-AUT

18 V cordless vacuum pump, 1/4" SAE port and 1/2" ACME adapter (without battery and adapter sleeve)

90058-BAT-KT-5A

Mastercool rechargeable battery and adapter sleeve

90058-BAT-5A

Mastercool rechargeable battery

90058-SL-MC

Adapter sleeve to allow for use with Mastercool batteries

MASTERCOOL BATTERY CHARGER

90058-CH: 110V Standard US cable 90058-CH-E: 220V Schuko cable 90058-CH-AUS: 220V Australia cable 90058-CH-BR: 220V Brazil cable











90058-BAT-5A



90058-SL-MC

^{*} Mastercool does not recommend this pump be used with any other battery