### Visit us at www.TestEquipmentDepot.com

## RecoverXLT2-AP™ Refrigerant Recovery System





# Designed to Meet Safety Requirements for R-32, R-1234yf and R-1234ze

The drive to lower global warming potential refrigerants with increased flammability has necessitated the evolution of the market leading YELLOW JACKET® RecoverXLTTM recovery machine: The new RecoverXLT2-APTM Refrigerant Recovery Machine with twin cylinder 1/2 hp oil less compressor and gravity drain condenser. The unique "ambient pressure switch" and three meter power cord comply with the current safety requirements. The RecoverXLT2-AP is specifically designed for the new lower GWP refrigerants including R-32, R-1234yf and R1234ze as well as the most common CFC, HFC and HFO refrigerants, including R-22, R-404A, R-407, R-410A, R-448A and R-449A.

Set yourself up to work smart. Surround yourself with the hardest working, highest performing tools available. The YELLOW JACKET RecoverXLT2-AP and other YELLOW JACKET service tools for the HVAC/R service professional.

Calculated Recovery Ratings							
	Kg./min			Kg./hour			
	Vapor	Push/Pull	Liquid	Vapor	Push/Pull	Liquid	
R-22	0.17	4.16	3.10	10	250	186	
R-32	0.11	3.41	2.53	7	205	152	
R-134a	0.20	4.20	3.14	12	252	188	
R-404A	0.30	3.66	2.73	18	220	164	
R-410A	0.18	3.7	2.77	11	222	166	
R-1234yf	0.17	3.83	2.86	10	230	171	
R-407C	0.18	3.99	2.98	11	240	179	

#### **Features**

- 1/2 hp, twin cylinder, oil-less compressor for fast recovery of Class III, IV and V refrigerants including R-32, R-1234yf and R-1234ze.
- Safe venting of case interior prior to start up.
- Low pressure switch stops recovery above ambient pressure for leaking systems to prevent pulling air into recovery cylinders.
- Low pressure bypass for recovery of leak-free systems. Patented single valve control for easy changeover from liquid to vapor to purge.
- Auto purge clears residual refrigerant for quick change from one refrigerant to another.
- Condenser with gravity drain keeps recovery tank up to 10° cooler for reliable operation in high ambient conditions.
- Lightweight case designed for easy carrying.
- One year warranty.
- Designed and manufactured in the U.S.A.



### **Specifications:**

Capabilities: Vapor, liquid, push/pull

Refrigerants: R-32, R-1234yf, R-1234ze as well as the

most common CFC, HFC and HFO refrigerants, including R-22, R-404A, R-407, R-410A, R-448A and R-449A

Compressor: ½ hp, twin cylinder, reciprocating, oil-less

Power Source: 230V - 50/60 Hz

Amps: 4.0

High Pressure Shut-Off: 517 psig/35 bar – auto reset Operating Temperature: 40° to 122° F (4° to 50° C)

Weight: 14.5 kg/32 lbs.

Dimensions: 19.3(w) x 12.4 (h) x 12.5 (d) in. 490 (w) x 315 (h) x 317 (d) mm

UPC#	Description	
95764	RecoverXLT2-AP™ Refrigerant Recovery System	
	230V/50-60 Hz (Euro, UK, NZ and Australian plug)	

