

# RIDGID®

## K9-12 FlexShaft® Machine

Clears From 1¼" to 2" (32 mm to 50 mm)  
Pipe Up to 30' (9 m)



The NEW RIDGID® FlexShaft K9-12 machine is the most compact version of the FlexShaft Drain Cleaning Machines. The fully enclosed housing contains 30' of FlexShaft cable, encapsulated in nylon sheath for less mess and easy cleanup. The lightweight, portable design is perfect for 1¼" - 2" pipes.

- **Wall-To-Wall Clean:** Chain knocker fully expands inside the pipe reaching wall-to-wall, clears the blockage and restores the pipe to full flow capacity
- **Less Mess & Quick Cleanup:** FlexShaft cable is fully enclosed in a flexible yet durable nylon-sheath and fully contained in housing for less mess and quick clean up
- **Intuitive Use & Ergonomic Design:** Powered by any standard 1800-2500 RPM cordless drill
- **Cable Protection System:** Built-in clutch design extends cable life to maximize uptime
- **Lightweight System:** Less than 10lb unit is a clear first choice to tackle slow or blocked drains
- **Adaptable Accessories:** Compatible with plain chains, carbide chains, penetrating heads, brushes and more

RIDGID® FlexShaft® cable is spun by attaching your cordless drill to the input shaft on the housing. As the cable spins, the chain knocker attached will expand to provide wall-to-wall pipe cleaning. Fast setup and cleanup, quick cleaning, and cordless convenience allow you to restore your pipes to full flow capacity as efficiently as possible.



## SPECIFICATIONS

- Model.....**K9-12**
- Drain Capacity (Nom.) .....1¼" to 2" (32 mm – 50 mm)
- Cable Diameter (without Sheath) .....¼" (6 mm)
- Cable Assy. Diameter (with Sheath).....¾" (9,5 mm)
- Cable Assembly Length .....30' (9 m)
- Rotational Speed.....Maximum 2500 RPM
- Drill Attachment .....5/16" Hex (8 mm)
- Weight (without Drill/Knocker).....8.4 lbs. (8,3 kg)
- Dimension (without Drill) .....4.83" x 12.91" x 15.06"  
(12,23 cm x 32,79 cm x 38,25 cm)
- Operating temperature.....20°F to 140°F (-6°C to 60°C)



## ORDER INFORMATION

CATALOG NO.	MODEL NO.	DESCRIPTION	WEIGHT (lb.) (kg)	
74978	K9-12	FlexShaft, 1¼" - 2" Pipes, Includes: 30' ¼" cable and kit*	8.4	3,8

\* K9-12 includes: K9-12 1 ¼" Chain Knocker, 3mm Hex Key, Manual Pack



### Smooth Chain Knockers

- For all pipe types
- For soft blockages and grease



### Carbide Tipped Chain Knockers

- For hard-walled pipes
- For scale, roots, grease and soft blockages



### Penetrating Carbide Tipped Chain Knockers

- For hard-walled pipes
- For wipes, scale, roots and soft blockages

## ACCESSORIES

CATALOG NO.	DESCRIPTION
64293	FlexShaft Chain Knocker, ¼" cable, 1¼" - 1½" pipe, single chain
64298	FlexShaft Chain Knocker, ¼" cable, 2" pipe, 2 chain
64283	FlexShaft Chain Knocker, ¼" cable, 1¼" - 1½" pipe, single chain, carbide tipped
64288	FlexShaft Chain Knocker, ¼" cable, 2" pipe, 2 chain, carbide tipped
66568	FlexShaft Chain Knocker, ¼" cable, 1¼" - 1½" pipe, single chain, carbide tipped w/penetrating head
66573	FlexShaft Chain Knocker, ¼" cable, 2" pipe, 2 chain, carbide tipped w/penetrating head
68933	1½" Nylon Brush, ¼" cable, 1½" pipe
68938	2" Nylon Brush, ¼" cable, 2" pipe
71838	Penetrating Ball Head, ¼" cable, 1¼" - 2" pipe
71843	Penetrating Drop Head, ¼" cable, 1¼" - 2" pipe
64338	RIDGID FlexShaft Lubricant
76183	FlexShaft Cable Assembly, ¼" x 30'
64363	RIDGID Modified Wallpipe 1¼"
64368	RIDGID Modified Wallpipe 1½"
64643	FlexShaft ¼" Sheath Stock, 12"

