

## ETFB10 Non-Contact AC Voltage and Optical Fiber Detector

*For single and multimode fiber, patch cords and ports*

### Features:

- Non-contact AC voltage range: 50 to 1000V
- Quickly determine the presence of fiber optic signals
- Audible/Visual alerts
- Built-in worklight at the tip and flashlight in the back
- Low battery indicator (<2.4V)
- Auto power off after 5 minutes
- CAT IV 1000V safety category
- Includes (2) AAA batteries

### Applications:

Easily check for the presence of AC Voltage before working on a circuit

Low voltage detector range for low power systems, process controllers, garage door openers, power relays, coils, alarm sensors and controls

Fiber Optic Detector determines the presence of fiber optic activity on single and multimode fiber, patch cords and ports



### Specifications

Voltage Range	50 to 1000VAC
Frequency Range	50/60Hz
Alarm Mode	Audible and Visual
Optical Fiber Detection Range	850 to 1700nm
Alarm Mode	Audible and Visual
Power	(2) AAA batteries
Safety Category	CAT IV 1000V
Dimensions	6.8 x 1.1 x 0.9" (172 x 27 x 23mm)
Weight	1.4oz (39g)

### Ordering Information:

ETFB10 Non-Contact AC Voltage and Optical Fiber Detector

