

Fully Insulated - 1000V Rated Adjustable Wrenches



- Wide capacity jaw allows each tool to work with more fastener sizes
- Wider handle provides more comfort and less stress to the hand
- Tension spring stabilizes jaw and allows easy adjustment of knurled adjustment knob
- Alloy steel and heat treated
- Proportioned dimensions for greatest strength and minimum weight
- Fully insulated adjustable wrench with NO exposed metal for complete 1000V Protection



AW-10FI

PN	DESC
AW-6FI.....	6" O.A.L. - .94" Opening
AW-8FI.....	8" O.A.L. - 1.13" Opening
AW-10FI.....	10" O.A.L. - 1.31" Opening
AW-10FI-ST.10"	With Loop
AW-12FI.....	12" O.A.L. - 1.56" Opening
AW-15FI.....	15" O.A.L. - 1.75" Opening

Insulated - Non-Voltage Rated Adjustable Wrenches



- Wide capacity jaw allows each tool to work with more fastener sizes
- Wider handle provides more comfort and less stress to the hand
- Tension spring stabilizes jaw and allows easy adjustment of knurled adjuster
- Alloy steel and heat treated
- Proportioned dimensions for greatest strength and minimum weight

***NOT A VOLTAGE RATED TOOL**



AW-10

PN	DESC
AW-4.....	4" O.A.L. - .69" Opening
AW-6.....	6" O.A.L. - .94" Opening
AW-6-C...	6" Chrome
AW-8.....	8" O.A.L. - 1.13" Opening
AW-8-C...	8" Chrome
AW-10.....	10" O.A.L. - 1.31" Opening
AW-10-C..10"	Chrome
AW-12.....	12" O.A.L. - 1.56" Opening
AW-12-C..12"	Chrome
AW-15.....	15" O.A.L. - 1.75" Opening
AW-15-C..15"	Chrome

Pipe Wrenches



- Oh Yes - We even have these
- Premium quality Rothenberger base tool with bump protection

***NOT A VOLTAGE RATED TOOL**



12PW

PN	DESC
8PW.....	8"
10PW.....	10"
12PW.....	12"

RATED 1000 VAC 1500 DC
Tested to 10,000 VAC and Rated for 1,000 VAC when working on or around live parts

Adjustable Wrenches

- Wide capacity jaw allows each tool to work with more fastener sizes
- Wider handle provides more comfort and less stress to the hand
- Tension spring stabilizes jaw and knurl adjusts easily
- Alloy steel and heat treated
- Proportioned dimensions for greatest strength and minimum weight



Specifications	AW-4	AW-6	AW-8	AW-10	AW-12	AW-15
Length	4"	6"	8"	10"	12"	15"
Weight	.25 lbs	.35 lbs	.60 lbs	1 lbs	1.5 lbs	3.35 lbs
Jaw Opening	.69"	.94"	1.13"	1.31"	1.56"	1.75"

NOTE: This style of adjustable wrench is not voltage rated.

Cementex double-insulated tools:

- Made in the U.S.A.
- Comply with the IEC 60900 standard
- Comply with ASTM F1505 standard
- Help you meet requirements of:
OSHA 1910.331-335 | NFPA 70E | CSA-Z462

Cementex

The Safety Tool Specialists