

ELECTRICAL SAFETY

INSTALLATION TESTERS



C.A 6011 - C.A 6011 KIT

Ref.: P0129992

P01191611

300 V Cat III









STRENGTHS

- Dedicated to continuity testing on protective earth conductors
- Double configuration: continuity tester attached to the reeler and remote continuity tester on the wrist
- Lightweight and compact
- Ergonomic to facilitate operators' work

ADDITIONAL INFO

Triple visual indications:

- Backlighting (blue / red)
- Symbols: "Confirmed box" / "X-barred box"
- Measurement value
- Buzzer
- Vibrator

CONTENTS

C.A 6011 KIT delivered with:

- 1 elastic strap for fixing the measuring unit to your wrist
- 1 waist belt + 1 shoulder belt
- \blacksquare 1 "Cable Reeler No. 01" with 1 green PVC cable 30 m long
- 1 black spiral PVC cable 3.5 m long
- 1 green crocodile clip with Ø 4mm banana socket
- 1 moulded black test probe
- 1 green PVC cable 0.50 m long
- 1 set of 4 x 1.5 V LR06 alkaline batteries

C.A 6011 delivered with:

- 1 elastic strap for fixing the measuring unit to your wrist
- 1 set of 4 x 1.5 V LR06 alkaline batteries

SPECIFICATIONS

	C.A 6011 - C.A 6011 KIT	
Display	2,000 counts with two-colour backlighting	
Continuity		
Measurement range	0.00 Ω to 2.00 Ω	2.00 Ω to 20.00 Ω
Resolution	10 mΩ	
Measurement current	200 mA	20 mA
	With automatic polarity reversal	
Open-circuit voltage	\pm (4 VDC < U < 6 VDC)	
Resistance		
Measurement range	1.0 Ω to 200.0 Ω	
Resolution	100 mΩ	
Measurement current	10 mA	
Open-circuit voltage	\pm (4 VDC < U < 6 VDC)	
Continuity threshold	Programmable: 1Ω or 2Ω	
Compensation of cable resistance	Yes	
Test conformity / non- conformity indication	Configurable: visual, audible or vibrating	
Compliance with standards	IEC 61557-1 & IEC 61557-4, IEC 61010-1, IEC 61010-2-030, 300V CAT IV	
Automatic standby	10 minutes / deactivatable	
Battery life	30,000 measurements in real use	
Power supply	4 x 1.5 V AA/LR6 batteries	
Dimension (instrument +reeler)	225 x 185 x 135 mm	
Weight	C.A 6011 alone: 350g Reeler with 30 m cable: 1.2 kg	

ACCESSORIES / REPLACEMENT PARTS

■ Cable reeler no. 1 - 30m	P01295492
Continuity rod	P01102084A
0 1111 ' 110	

See all the accessories on page 110