

# SJ-HS



**AND**  
A&D Weighing

# SJ-HS

Food service, Stores, Post offices, Industries, Factories, Schools, Laboratories, Warehouses, Offices, Home use and a wide range of other diverse weighing applications are possible.


- **Stainless steel weighing pan**
- Fast stability time – Less than 1 second
- Large wide LCD display (1 inch height)
- Durable body
- Large weighing pan 9 in x 7 in
- Full digital calibration function
- Multiple weighing units – g, lb, oz and lb-oz
- Battery operation with 4 x D size dry batteries
- Simple and easy to change the batteries
- Optional AC adapter
- Automatic power OFF function
- Spirit level and adjustable feet for accurate weighing
- Status indication function – Battery, Stable, Zero and Net



SJ-HS Specifications		SJ-1000HS	SJ-2000HS	SJ-5000HS	SJ-5001HS	SJ-12KHS	SJ-20KHS	SJ-30KHS
Capacity x Resolution	g	1000g x 0.5g	2000g x 1g	5000g x 2g	5000g x 1g	12kg x 0.005kg	20kg x 10g	30kg x 20g
	lb	2.2lb x 0.001lb	4.4lb x 0.002lb	11lb x 0.005lb	11lb x 0.005lb	26lb x 0.01lb	44lb x 0.02lb	66lb x 0.05lb
	oz	35oz x 0.02oz	70oz x 0.05oz	176oz x 0.1oz	176oz x 0.1oz	423oz x 0.2oz	705oz x 0.5oz	1058oz x 1oz
	lb-oz	2.2lb x 0.1 oz	4.4lb x 0.1 oz	11lb x 0.1oz	11lb x 0.1oz	26lb x 1 oz	44lb x 1 oz	66lb x 1oz
Linearity	1g	2g	5g	5g	10g	20g	20g	20g
Repeatability (S.D.)	1g	2g	5g	5g	10g	20g	20g	20g
Span drift	0.015% / C TYP ( 5C~35C/ 41F~95F)							
Display	Liquid Crystal Display , 25mm / 0.98 inches							
Operating temperature	—10C~40C / 14F~104F, less than 85% RH (No condensation)							
Display update	Approx. 10 times per second							
Power	4 x R20P / LR20 / "D" size batteries or AC adapter							
Battery life	Approx. 800 hours with alkaline cells at 20C / 68F							
Pan size	230 (W) x 190 (D) mm / 9.05 (W) x 7.48 (D) inches							
Dimensions	265 (W) x 250 (D) x 103 (H) mm / 10.4 (W) x 9.8 (D) x 4.1 (H) inches							
Weight	Approx. 2.1kg / 4.6lb							
Calibration mass	1000g	2000g	5000g	5000g	10kg	20kg	20kg	30kg

Specifications subject to change for improvement without notice

## External Dimensions (mm/inches)



## Accessories

- |           |            |                      |
|-----------|------------|----------------------|
| AX-TB164B | AC adapter | AC230V "C" type plug |
| AX-TB173A | AC adapter | AC230V "BF" plug     |
| AX-TB196  | AC adapter | AC100 "A" type plug  |
| AX-TB202  | AC adapter | AC120 "A" type plug  |