
## **DIFFERENTIAL PRESSURE ANEMOMETER** Bi-Directional Anemometer, No Sensing Electronics



The **MODEL ANE-1** Differen ial Pressure Anemometer is a robust and durable bidirectional anemometer with no moving parts or sensing electronics. Using the installed tubing, the ANE-1 connects easily to any manometer or applicable pressure sensing device and is capable of measuring a wide velocity range. The air velocity range and accuracy is dependent on the installed manometer, and the ANE-1 retains the accuracy as long as it is dust free.

## FEATURES/BENEFITS

- · Wide velocity range dependent on connected manometer
- Includes 5' of blue and 5' of red silicone tubing with a removable adapter sized 2 mm OD to 3/16" OD

## APPLICATIONS

· Measure face air velocity on grills, diffusers, registers, exhaust hoods

## SPECIFICATIONS

Service: Clean air only. Wetted Materials: Anemometer: ABS; Tubing: Silicone; Handle: Phenolic. Dimensions: Tubing: 2 mm ID x 4.5 mm OD; Adapter: 2 mm OD to 3/16" OD connections. Temperature Limits: 23 to 122°F (-5 to 50°C). K-Factor: 0.843. Process Connections: 2 removable 5" (12.7 cm) tubing 3/16" ID. Weight: 7.7 oz (220 g).

MODEL CHART	
Model	Description
ANE-1	Differential pressure anemometer

Test Equipment Depot - 800.517.8431 - 99 Washington Street Melrose, MA 02176

TestEquipmentDepot.com