



# QUADROCKER™

- High capacity rocker, accepts up to 4 tiers
- User-adjustable platform configuration
- Adjustable rocking speed and tilt angle
- Incubator and cold room safe
- Includes four large (16 x 12in.) platforms

Benchmark's QuadRocker features a unique, tiered attachment system that accepts up to four platforms. Unlike traditional single platform rockers, the QuadRocker includes a base level as well as three additional stacking platforms, providing a total work-surface of over 750 sq. in.

For most gel blotting, washing and staining applications, the rocker can be installed with all four rocking platforms. For applications requiring larger vessels, the quantity and height of the platforms can easily be customized to provide a maximum clearance of up to 8¼ in (21cm). The QuadRocker's versatility is further enhanced by digital speed and timer control, as well as user-adjustable tilt angle.

The compact footprint and unmatched capacity of the QuadRocker make it the efficient way to rock!

## Ordering Information:

BR5404\* *QuadRocker™* with four non-slip rubber mat platforms (16x12 in.)

\* 115V with US plug. For 230V with EU plug, please add (-E) to item number.



Add/remove platforms to create the ideal capacity and spacing for your application (up to 8¼ in. clearance)

## Technical Data:

Speed Range:	<b>5 to 80 rpm</b>
Tilt Angle:	<b>6 to 22° (user adjustable)</b>
Platform Size:	<b>16 x 12 in. / 40.5 x 30cm</b>
Load Capacity:	<b>12 lb total / 5.45 kg total</b>
Clearance:	<b>Max. with 2 platforms: 8¼"</b> <b>Max. with 4 platforms: 2¼"</b>
Dimensions:	<b>16 x 13.5 x 8 in.</b> <b>40.6 x 34.2 x 20.3 cm</b>
Operating Temp.:	<b>0°C to +50°C</b>
Weight:	<b>27 lb / 12 kg</b>
Electrical:	<b>115V or 230V, 50-60Hz</b>
Warranty:	<b>2 years</b>