

Features:

- True RMS measurement.
- AC/DC voltage, AC/DC current, resistance, Capacitance, diode check, duty cycle, NCV, frequency measurement.
- Auto ranging.
- Data hold function.
- Relative Mode.
- Low battery indication.
- Display backlight.
- Jaw Capacity 30 mm.
- Auto Power Off.
- Continuity Buzzer.
- LED flashlight.
- Safety standard: IEC/EN 61010-1
IEC/EN 61010-2-032, IEC/EN 61010-2-033
CAT III 600V, Pollution grade: 2.

Technical Specification:

BST-CM74	
AC Current	40A / 400A ±(2.5%+5)
DC Current	40A / 400A ±(2.0%+3)
AC Voltage	4V / 40V / 400V / 600V ±(1.2%+5)
DC Voltage	400mV / 4V / 40V / 400V / 600V ±(0.8%+1)
Resistance	400Ω / 4kΩ / 40kΩ / 400kΩ / 4MΩ / 40MΩ ±(1.0%+2)
Capacitance	40nF / 400nF / 4μF / 40μF / 400μF / 4mF / 40mF ±(4.0%+5)
Frequency	10Hz-1MHz ±(0.1%+4)
Temperature	-40 °C ~ 1000°C ±(1.0%+3), -40°F~1832°F ±(1.0%+6)
Display Count	4000
Jaw Capacity	30mm
LCD Size	38mm × 24 mm
Power Source	AAA 1.5V × 3
Dimensions	228 × 77 × 41 mm
Weight	Approx. 265g (battery included)
Accessories	Instruction manual, Battery, Test Lead, Carrying Bag, Temperature Probe



BST-CM74

Ordering Information:

- BST-CM74: 400A True RMS AC/DC Clamp Meter + NCV.