

BESANTEK Heat Stress WBGT DataLogger (Temperature - Humidity - Dew Point - Wet Bulb - WBGT) Widely Applied to Laboratory Fields, Food Industry, Medical Application, Pharmaceutical Industry, Industrial Application, Environmental Protection Areas, and Agricultural Research Fields.

Features:

- Adopt high sensitive sensor with fast response and high accuracy.
- Built-in micro SD socket stores all parameters.
- Calculate dew point, wet bulb, WBGT temperature in seconds.
- Selectable °C or °F.
- Red/Green indicator light (Alert).
- 1.5V AAA size batteries.
- Store up to 8G memory (Supplied).
- Export SD data to csv. format.
- Large size LCD display with date & time.
- Maximum, Minimum, current value, recall function.
- Offset adjust for Temperature & Humidity.
- Audible / visible alarm.
- Date & Time.
- Alarm threshold adjust.
- Logging icon.
- Desktop or wall mount meter.



Technical Specification:

BST-DL77	
Internal Temperature Range	0 ~ 50 °C (32~122 °F)
Internal Temperature Resolution	0.1 °C (0.1 °F)
Internal Temperature Accuracy	± 0.5 °C (± 1.2 °F)
External Temperature Range	-40 ~ 85 °C (-40~185 °F)
External Temperature Resolution	0.1 °C (0.1 °F)
External Temperature Accuracy	± 0.5 °C (0 ~50 °C), others ± 1 °C
Humidity Range	0 ~ 99.9 %RH
Humidity Resolution	0.1%RH
Humidity Accuracy	± 3%RH (at 25°C,30~70%RH, others ± 5 %RH)
Power Source	1.5V AAA size batteries
Dimensions	113 x 108 x 28 mm (L x W x H)
Accessories	Instruction manual, AAA Batteries x 4pcs, Universal Adapter, External TRH Probe

BST-DL77



Universal Adapter

Ordering Information:

- BST-DL77: Heat Stress WBGT DataLogger (Temperature - Humidity - Dew Point - Wet Bulb - WBGT).