

BESANTEK Telescopic Hot Stick provides maximum flexibility and access electrical systems from a safe working distance. Select from seven different models that cover up to forty feet. The high grade fiberglass construction.

## Features:

- Triangular-shaped design keeps the sections aligned during extension and retraction.
- Push button release for stick extension and retraction.
- Telescopic design allows for easy assembly, storage and transportation.
- Withstands voltage rating of 100kV from 30cm for 5 minutes.
- Universal end fitting accepts a wide variety of standard attachments.
- Highly visible yellow tip section.
- Easy-to-replace sections.
- Carrying bag included.
- Optional integrated height measurement scale.
- Accessories: Instruction manual, carrying bag, disconnect hook and fuse extractor head (optional).

## Applications:

- Voltage detection.
- Opening and closing switches.
- Overhead switch operation.
- Fuse replacement.
- Lamp replacement.
- Cleaning electrical fittings.
- Installation of temporary clamps.
- Tree trimming.



## Accessories



Disconnect Hook



**BST-HVD12B**

Fuse Extractor Head (Optional)



Carrying Bag



**BST-HVD20-Series**

## Technical Specification:

BST-HVD20-Series							
Model	BST-HVD20-3	BST-HVD20-4	BST-HVD20-5	BST-HVD20-6	BST-HVD20-7	BST-HVD20-8	BST-HVD20-9
Sections	3	4	5	6	7	8	9
Extended Length (m)	3.82	5.10	6.42	7.78	9.18	10.62	12.09
Retracted Length (m)	1.48	1.53	1.58	1.63	1.68	1.73	1.78
Stick Width (mm)	37.8	41.8	45.3	49.5	53	57.5	61.5
Weight (kg)	1.85	2.40	3.10	3.85	4.70	5.90	6.90

## Ordering Information:

- BST-HVD20-Series: Telescopic Hot Stick.
- BST-HVD12B: Fuse Extractor Head.



**Safety Standard:**  
• IEC 62193