

BESANTEK Digital Multimeter is designed with all function you need with high accuracy and double molded rubber housing.

## Features:

- 3-3/4 digital LCD with a max. display of 3999.
- An angled-display design helps the user to identify the reading of value easier.
- Auto-ranging designed.
- Range change function.
- Voltage measurement.
- Current measurement.
- Resistance measurement.
- Frequency measurement.
- Continuity check.
- Diode measurement.
- Data hold function.
- Low battery warning indicator.
- Over range indication.
- Fuse protection.
- Hook design included makes it easy to use no matter for standing or hanging purpose.
- Accessories: Instruction manual, test leads, batteries and holster.



**BST-MT266**

## Accessories



## Technical Specification:

BST-MT266						
DC Voltage	Range	400.0mV	4.000V	40.00V	400.0V	1000V
	Resolution	100μV	1mV	10mV	100mV	1V
	Accuracy	±(0.5%rdg+3dgt)				
	Input Protection	1000V DC				
	Input Impedance	10MΩ				
AC Voltage	Range	400.0mV	4.000V	40.00V	400.0V	750V
	Resolution	100μV	1mV	10mV	100mV	1V
	Accuracy	±(1%rdg+5dgt)				
	Input Protection	800V AC				
	Input Impedance	10MΩ				
DC Current	Range	400.0μA	4000μA	40.00mA	400.0mA	10A
	Resolution	0.1μA	1μA	0.01mA	0.1mA	10mA
	Accuracy	±(1%rdg+5dgt)				
	Input Protection	500mA				
	OL Protection	0.5A/250V fast blow fuse for 400mA 12.5A/500V fast blow fuse for 10A				
AC Current	Range	400.0μA	4000μA	40.00mA	400.0mA	10A
	Resolution	0.1μA	1μA	0.01mA	0.1mA	10mA
	Accuracy	±(1%rdg+5dgt)				
	Input Protection	500mA				
	OL Protection	0.5A/250V fast blow fuse for 400mA 12.5A/500V fast blow fuse for 10A				
Resistance	Range	400.0Ω	4.000kΩ	40.00kΩ	400.0kΩ	4.000MΩ
	Resolution	0.1Ω	1Ω	10Ω	100Ω	1kΩ
	Accuracy	±(1.5%rdg+3dgt)				
	Max. Test Current	0.52mA				
	Max. Open Circuit Volt.	0.25V				
	OL Protection	500V DC				
Frequency	Range	4.000kHz	40.00kHz	400.0kHz	4.000MHz	40.00MHz
	Resolution	1Hz	10Hz	100Hz	1kHz	10kHz
	Accuracy	±(1%rdg+2dgt)				
Continuity	Range	400.0Ω				
	Resolution	0.1Ω				
	Beeper	< 25Ω				
	Test Current	0.52mA				
Operating Temperature & Humidity	0°C~40°C, 80%RH max.					
Storage Temperature & Humidity	-10°C~50°C, 80%RH max.					
Power Source	1.5V (AAA) × 2					
Dimensions	192 (L) x 88.6 (W) x 45.2 (D) mm					
Weight	Approx. 350g (battery included)					

## Ordering Information:

- BST-MT266: Digital Multimeter.



**Safety Standard:**

- EN 61010-1 CAT III 600V, EN 61326-1