

Features:

- Infrared to measure surface temperature.
- Triple digital LCD display.
- Slim design with rubberized sides for better grip and for one hand operation.
- Low battery warning indicator.
- Fast response time.
- Accurate reading.
- Red laser indication.
- Dual display & backlight.
- Simultaneous display of: humidity/temperature, humidity/dew point, humidity/wet bulb.
- Highest 30 to 1 distance to target ratio measures smaller surface areas at greater distance.
- Accessories: instruction manual, 9V battery, PC software CD, USB interface cable, type K temperature probe and carrying case.

Technical Specification:

BST-SQ01		
Type K Temperature	Range	-100~1372°C (-148~2501°F)
	Resolution	0.01°C/°F
	Accuracy	±3% ±0.20m/s
InfraRed Temperature	Range	-50 to 500°C (-58 to 932°F)
	Resolution	0.1°C/°F
	Accuracy	-50 to -20°C (-58 to -4°F): ±5.0°C (9.0°F), -20 to 500°C (-4 to 932°F): ±2% reading or ±2°C (4°F)
Air Temperature	Range	-10~60°C (14~140°F)
	Resolution	0.01°C/°F
	Accuracy	±2.0°C (4.0°F)
Humidity	Range	0%~99.9%RH
	Resolution	0.1%RH
	Accuracy	±2%RH
Dew Point Temp.	Range	-68°C~60°C (-90.4°F~140°F)
	Resolution	0.1°C/°F
	Accuracy	±0.5°C/0.9°F
Wet Bulb Temp.	Range	0°C~80°C (32°F~176°F)
	Resolution	0.1°C/°F
	Accuracy	±0.5°C/0.9°F
Power Source	9V battery	
Dimensions	255mm x 75mm x 50mm	
Weight	350g	

Ordering Information:

- BST-SQ01: Psychrometer with InfraRed Thermometer.



BST-SQ01



Accessories