

200A AC OPEN JAW FORK METER

CL360

UP TO 3/0 CABLE*

Cable diameters up to 0.58" (14.7 mm)

True RMS
Measurement
Technology

600V ~
1000V =|=
200A ~
60M Ω



3 m



IP40

CAT III
600V

CAT II
1000V





200A AC OPEN JAW FORK METER

The CL360 is an automatically ranging true root mean squared (TRMS) digital, open jaw fork meter that measures AC current via the fork, AC/DC voltage, continuity, and resistance via test leads. It can also detect the presence of voltage using its integrated non-contact voltage (NCV) tester. The wide jaw allows for current measurements in wires and cables up to 3/0.

Test lead holders
behind fork for natural
two-handed operation

| Measurement | CL360 |
|---|------------------------------|
| AC Voltage | 600V |
| DC Voltage | 600V |
| AC Current | 200A |
| Resistance | 60MΩ |
| True RMS | ● |
| Audible Continuity | ● |
| Backlight | ● |
| Non-Contact Testing | ● |
| Auto-Ranging | ● |
| Data Hold | ● |
| LCD Display Count | 6000 |
| Durability | |
| Ingress Protection | IP40 |
| Drop Protection | 9.8 ft. (3 m) |
| Safety Rating — Jaw & Housing | CAT IV 600V CAT III 1000V |
| Safety Rating — Electrical & Protection Circuit | CAT III 600V CAT II 1000V |

Wide Jaw for measuring current in cables up to 3/0*

Non-Contact Voltage (NCV) sensor integrated into the jaw detects AC voltages > 70V AC RMS

Function Switch textured and positioned for ease of use

Non-Contact Voltage (NCV) Button

Backlit display for clear visibility in low light environments

Data Hold, Backlight Button



Built-in test lead holders on back of meter for one-handed use

Includes:

- Owner's Manual
- Carrying Case
- Straight Input Test Leads
- 2 x AAA Batteries



| Cat. No. | UPC# 0-92644+ | Description | Height | Weight (with Batteries) |
|----------|---------------|-----------------------------|----------------|-------------------------|
| CL360 | 69114-0 | 200A AC Open Jaw Fork Meter | 8.39" (213 mm) | 7.3 oz. (208 g) |

*Cable diameters up to 0.58" (14.7 mm)

