

Accessories

■ **Supplementary Products**

Item	Model	Specification	Applicable model
Carrying case	RB057	Soft type	30031

■ **Optional Accessories**

Item	Model	Specification	Applicable model
Output Cable for Terminal Screw	91019	Cable length: approx.1.1m	CL150,CL155 CL250,CL255
Output Cable with Banana Plug	91020	Cable length: approx.2.0m	CL360
Clamp Adapter	99025	Ratio/Range = 10:1/3000A	CL120,CL130,CL135,CL150, CL155,CL220,CL235,CL250, CL255,CL320,CL340,CL345

■ **99025 Specifications**

Item	Specifications
Measuring Range	0 ~ AC3000A
Ratio/Range	10:1 (input to output)
Accuracy	±2% of input ±0.5A
Allowable Measurement Time	0 ~ 1000A(continuous), 1000 ~ 1500A(10 minutes max.), 3000A(30 seconds max.)
Conductor Size	100mm max. (100×150mm)
Frequency Response	50Hz/60Hz
Safety Standard	EN61010-1 CAT.III300V Pollution Degree 2
Withstand Voltage	AC3700V for 1 minute
Dimensions	150(W)×317(H)×33(D)mm 40(W)×45(H)×10(D)mm Output coil
Weight	Approx. 750g
Accessories	93035(Carrying Case)
For use with following models	

■ **Supplementary Products**

Item	Model	Specification	Applicable model
Test Lead	98010	Angle Plug type	CL130,CL135,CL235
Test Lead	98011	Straight Plug type	CL150,CL155,CL250,CL255
Output Plug	98012	3pcs/set	CL150,CL155,CL250,CL255
Carrying Case	93030	Hard type	CL340,CL345
Carrying Case	93031	Soft type	CL360
Carrying Case	93032	Soft type	CL130,CL135,CL235
Carrying Case	93033	Soft type	CL120,CL220,CL320
Carrying Case	93034	Soft type	CL150,CL155,CL250,CL255
Carrying Case	93035	Hard type	99025

Clamp Adapter : 99025



Output Cable for Terminal Screw : 91019



Output Cable with Banana Plug : 91020

