

# Honeywell E-Mon

# Honeywell E-Mon CLASS 2000 3-Phase KWH/Demand Meter

## PRODUCT DATA

MMU Style  
(Multiple Meter Unit)  
MMU8, 16 or 24



Stand-Alone Configuration  
Dim: 6 3/4" H x 5 3/16" W x 3 1/4" D

- Non-volatile Memory.
- UL/CUL Listed.
- Revenue Grade Accuracy. Certified by independent test lab to ANSI C12.20 national accuracy standards. (+/- 0.2% from 1% to 100% of rated load.)
- California CTEP approved for use with solid-core current sensors. Listed by the California Energy Commission.
- Con Edison approved for RSP program.

## MODEL NUMBERS

Table 1. 120/208-240V, 3-Phase.

Amperage	KWH Meter	KWH/Demand Meter
100 Amp	E20-208100-JKIT	E20-208100-J-D-KIT
200 Amp	E20-208200-JKIT	E20-208200-J-D-KIT
400 Amp	E20-208400-JKIT	E20-208400-J-D-KIT
800 Amp	E20-208800-JKIT	E20-208800-J-D-KIT
1600 Amp	E20-2081600JKIT	E20-2081600J-D-KIT
3200 Amp	E20-2083200JKIT	E20-2083200J-D-KIT

Table 2. 277/480V, 3-Phase.

Amperage	KWH Meter	KWH/Demand Meter
100 Amp	E20-480100-JKIT	E20-480100-J-D-KIT
200 Amp	E20-480200-JKIT	E20-480200-J-D-KIT
400 Amp	E20-480400-JKIT	E20-480400-J-D-KIT
800 Amp	E20-480800-JKIT	E20-480800-J-D-KIT
1600 Amp	E20-4801600JKIT	E20-4801600J-D-KIT
3200 Amp	E20-4803200JKIT	E20-4803200J-D-KIT

Table 3. 347/600V, 3-Phase.

Amperage	KWH Meter	KWH/Demand Meter
100 Amp	E20-600100-JKIT	E20-600100-J-D-KIT
200 Amp	E20-600200-JKIT	E20-600200-J-D-KIT
400 Amp	E20-600400-JKIT	E20-600400-J-D-KIT
800 Amp	E20-600800-JKIT	E20-600800-J-D-KIT
1600 Amp	E20-6001600JKIT	E20-6001600J-D-KIT
3200 Amp	E20-6003200JKIT	E20-6003200J-D-KIT

## FEATURES

- Direct-read 2-line alpha-numeric LCD display without multiplier displays cumulative kWh & "real-time" kW load.
- Demand option displays kW/Demand and kW Peak date and time (15 minute interval standard, 30 minute interval available.)
- Available in MMU (Multiple Meter Unit) enclosures containing up to 24 meters in one compact enclosure.
- Patented 0-2 volt output split-core current sensors promote enhanced safety and accurate remote mounting of current sensors up to 2,000 feet from meter without power interruption. (Optional solid-core sensors available for 100 & 200 Amp meters.)
- Onboard installation diagnostics & verification system.
- Parallel up to three (3) sets of current sensors for cumulative reading.
- Meter can be used on the following configurations:
  - 3-Phase, 4-Wire
  - 3-Phase, 3-Wire
  - For other configurations contact factory.
- Fixed kWh pulse output
- Industrial JIC steel enclosure (standard) with padlocking hasp & mounting flanges for indoor installation. Knockouts 1 1/16" (3/4" cond.) bottom, 7/8" (1/2" cond.) top.
- Optional NEMA 4X polycarbonate enclosure with padlocking hasp & mounting flanges for indoor/outdoor installation (stand alone) with one 1 1/16" KO on bottom of enclosure.



## Optional Meter Enclosures

Replace “J” in model number with optional enclosure specification.

Specification M - MMU Configuration  
(ex. E20-208100-MKIT)

Specification R - NEMA 4X Raintight Enclosure  
(ex. E20-6001600RKIT)

NOTE: All meter kits include one set of three (3) split-core current sensors

## SPECIFICATIONS

- Meter shall be fully electronic with a 2-line alpha-numeric LCD display without multiplier displaying cumulative kWh and “real-time kW load. Meter shall provide rate of consumption indication and also a test sequence to ensure integrity of the display.
- Meter shall be optionally available with kW/Demand and kW peak date and time displays. (15 minute interval standard, 30 minute interval available.)
- Meter shall provide a load indicator to indicate real-time consumption levels for field testing and certification.
- Meter shall provide current sensor installation diagnostics indicator.
- Meter shall use 0-2 volt output current sensors to allow paralleling and/or mounting up to 2,000 feet from the meter. Sensors shall be of split-core configuration to allow installation without powering down. Sensors shall

- be available from 100 amp to 3200 amp. Sensors shall be optionally available in solid-core configuration (100 & 200 amp.)
- Meter shall be enclosed in a heavy-duty JIC steel enclosure suitable for indoor installation. Meter enclosure provides a method of locking to prevent unauthorized access.
- Meter shall be optionally available in an outdoor NEMA 4X polycarbonate enclosure with padlocking hasp & mounting flanges for indoor/outdoor installation.
- Meter shall be optionally available in MMU (Multiple Meter Configuration) enclosures containing up to 24 meters in one compact enclosure.
- Meter shall be UL Listed/CUL Listed to latest applicable standards for safety.
- Meter shall be certified by a nationally recognized independent test facility to ANSI C12.20 (+/- 0.2% from 1% to 100% of rated load) specifications with split-core current sensors.
- Meter shall be California CTEP approved for use with solid-core current sensors, listed by the California Energy Commission, and Con Edison approved for RSP program.
- Meter shall be provided with a non-volatile memory to maintain reading during power outages.
- Meter shall be provided with modular connector(s) to provide interfacing with:
  - AMR (Automatic Meter Reading)
  - Building Management/Energy Management Systems
- Meters shall be compatible with Honeywell E-Mon Energy™ software.

## ORDERING INFORMATION

When purchasing replacement and modernization products from your TRADELINE® wholesaler or distributor, refer to the TRADELINE® Catalog or price sheets for complete ordering number. If you have additional questions, need further information, or would like to comment on our products or services, please write or phone:

By using this Honeywell literature, you agree that Honeywell will have no liability for any damages arising out of your use or modification to, the literature. You will defend and indemnify Honeywell, its affiliates and subsidiaries, from and against any liability, cost, or damages, including attorneys' fees, arising out of, or resulting from, any modification to the literature by you.

Test Equipment Depot - 800.517.8431 - TestEquipmentDepot.com