

## Honeywell E-Mon

# Honeywell E-Mon Green Class Net Meter

### SPECIFICATION DATA



Dimensions: 7 1/4" H x 7" W x 3 1/4" D

## FEATURES

- **Advanced 4-line display showing:**
  - kWh delivered, received and Net kWh
  - kW demand (with peak date & time)
  - Power factor per phase
  - Real-time load in kW
  - Amps per Phase
  - Volts per phase
  - On-board set-up option for:
    - IP address
    - Meter date/time
    - ID codes for EZ7, Modbus and BACnet
- 0-2 volt output split-core current sensors allow for enhanced safety and accurate remote mounting of sensors up to 500 feet from meter without power interruption. (Optional solid-core sensors available.)
- Onboard installation diagnostics and verification system.
- Two external meter inputs (water, gas, BTU, etc.) Channels 5 & 6. Pulse count registers not visible on the LCD display may be read via E-Mon Energy, BACnet, Modbus or LonWorks front end.
- Phase loss alarm. (N.O. Contact)
- Built-in RS-485 communication capability supports the following connection configurations (or combinations not to exceed 52 devices per channel):
  - Up to 52 Class 3200, 3400 and 5000 meters and/or IDR interval data recorders
  - Cabling is daisy chain configuration, 3-cond., 22 AWG, up to 4,000 cable ft total per channel.
- **Communications:**
  - Built-in RS-485 and Ethernet
- **Protocols:**
  - EZ7
  - Modbus RTU
  - Modbus TCP/IP
  - BACnet MS/TP\*
  - BACnet IP\*
- NOTE: Interval data not available via BACnet.
- Records kWh and kVARh delivered, kWh and kVARh received in first four channels. Data stored in 15-minute intervals for up to 72 days or 5-minute intervals for up to 24 days. Maintains data in a first-in, first-out format.
- Compatible with E-Mon Energy software via EZ7 protocol for automatic meter reading, energy billing and profiling.
- Meter is designed for use on both 3-phase, 3-wire (delta) and 3-phase, 4-wire (wye) circuits. Optional single-phase, 3-wire configuration available.
- Green JIC Steel enclosure with padlocking hasp & mounting flanges for indoor installation with one 1-1/16" KO (3/4" cond.) on bottom of enclosure available
- Optional gray NEMA 4X polycarbonate enclosure available with padlocking hasp & mounting flanges for indoor/outdoor installation (stand alone) with one 1-1/16" (3/4" cond.) KO on bottom of enclosure.
- UL/CUL listed. Meets or exceeds ANSI C12.20 national accuracy standards. (+/- 0.2% from 1% to 100% of rated load)
- CE Mark approved.
- Meter meets or exceeds MID accuracy standards.
- BACnet protocol is BTL certified.
- MV-90 compatible (with EZ7 only.)



## MODEL NUMBERS

**Table 1. 120/208-240V, 127/220V, 3-Phase**

Model	Amperage
E50-208100-J01-N-KIT	100 amp
E50-208200-J01-N-KIT	200 amp
E50-208400-J01-N-KIT	400 amp
E50-208800-J01-N-KIT	800 amp
E50-2081600J01-N-KIT	1600 amp
E50-2083200J01-N-KIT	3200 amp

**Table 2. 220/380V, 230/400V, 240/415V, 3-Phase.**

Model	Amperage
E50-400100-J01-N-KIT	100 amp
E50-400200-J01-N-KIT	200 amp
E50-400400-J01-N-KIT	400 amp
E50-400800-J01-N-KIT	800 amp
E50-4001600J01-N-KIT	1600 amp
E50-4003200J01-N-KIT	3200 amp

**Table 3. 277/480V, 3-Phase.**

Model	Amperage
E50-480100-J01-N-KIT	100 amp
E50-480200-J01-N-KIT	200 amp
E50-480400-J01-N-KIT	400 amp
E50-480800-J01-N-KIT	800 amp
E50-4801600J01-N-KIT	1600 amp
E50-4803200J01-N-KIT	3200 amp

**Table 4. 347/600V, 3-Phase 4 - Wire.**

Model	Amperage
E50-600100-J01-N-KIT	100 amp
E50-600200-J01-N-KIT	200 amp
E50-600400-J01-N-KIT	400 amp
E50-600800-J01-N-KIT	800 amp
E50-6001600J01-N-KIT	1600 amp
E50-6003200J01-N-KIT	3200 amp

### Enclosure Options

Meters supplied standard in Green JIC Steel enclosures.

Not available in MMU Configuration.

To order a Gray NEMA 4X outdoor enclosure replace “J” in model number with “R” (E50-208100-R01-N-KIT)

### Communication Protocol & Option Packages

The models above represent the O1 protocol package. To specify a different protocol package replace “O1” in model number with the specification below.

RS-485 Port	Ethernet Port	Specify
EZ7	EZ7 Ethernet	O1
Modbus RTU	EZ7 Ethernet	O2
BACnet MS/TP	EZ7 Ethernet	O3
EZ7	Modbus TCP/IP	O4
EZ7	BACnet IP	O5
Modbus RTU	Modbus TCP/IP	O6

### Options

Three-phase meter kits are supplied with (3) split-core current sensors.

To order a single-phase, 3-wire meter kit replace “-N-” with “NSP” in the model number. Ex. E50-208100-J02NSPKIT

Single-phase meters will be supplied with (2) split-core current sensors.

## GREEN CLASS NET SMART METER SPECIFICATIONS

- Meter shall be fully electronic with 4 line LCD display showing:
  - kWh delivered, received and net kWh
  - kW demand (with peak date and time)
  - Power factor per phase
  - Real-time load in kW
  - Amps per phase
  - Volts per phase
- Meter shall utilize 0-2 volt AC output current sensors to allow paralleling and/or mounting up to 500 feet from meter.
- Sensors shall be of split-core configuration to allow installation without disconnecting cabling, etc. Sensors shall be available from 100 amp to 3200 amp. Sensors shall be optionally available in solid-core configuration (100 & 200 amp.)
- Meter shall provide current sensor installation diagnostics indicator, phase error indicator and phase angle diagnostics on display.
- Meter shall be field programmable for meter date/time, IP address and ID code for communication options.
- Meter shall be enclosed in a green heavy duty JIC steel enclosure with padlocking hasp and mounting flanges for indoor installation. Optional gray NEMA 4X polycarbonate enclosure available with padlocking

hasp & mounting flanges for indoor/outdoor installation (stand alone) with one 1-1/16" KO (3/4" cond.) on bottom of enclosure.

- Meter shall be UL/CUL listed to latest applicable standards for safety.
- Meter shall meet or exceed ANSI C12.20 accuracy standards.
- Meter shall be CE Mark approved.
- Meter shall meet or exceed MID accuracy standards.
- Meter shall provide non-volatile memory to maintain reading during power outages.
- Meter shall store interval data for kW and kVAR for up to 72 days in first-in first-out format. Interval data not available via BACnet.
- Meter shall be optionally available in single-phase, 3-wire configuration.
- **Meter shall operate as slave device when used with Modbus or LonWorks options. Meter works as a master device on BACnet MS/TP.**
- **Meter shall provide optional 5th & 6th channel for logging inputs from third-party metering devices (gas, water, BTU, etc.) Both channels provide interval data logging that can be read via Honeywell E-Mon Energy software and Modbus.**
- Meter shall be capable of daisy-chain connection using RS-485 EZ7 communications in combinations of Class 3200s, 3400s, 5000s, IDR-8s, IDR-16s

16s not to exceed 52 devices. Cabling shall be through RJ-11 modular jack (4-conductor) or terminal block (3-conductor), 22 AWG, up to 4,000 cable feet total.

- Meter shall be available with the following communication protocol & option packages:

<b>RS-485 Port</b>	<b>Ethernet Port</b>	<b>Specify</b>
EZ7	EZ7 Ethernet	01
Modbus RTU	EZ7 Ethernet	02
BACnet MS/TP	EZ7 Ethernet	03
EZ7	Modbus TCP/IP	04
EZ7	BACnet IP	05
Modbus RTU	Modbus TCP/IP	06

- BACnet protocol shall be BTL certified.
- Meter shall be MV-90 compatible (With EZ7 Only)

Test Equipment Depot - 800.517.8431 - TestEquipmentDepot.com

**Home and Building Technologies**

**Honeywell E-Mon**

® U.S. Registered Trademark  
© 2019 Honeywell International Inc.  
38-00070-01 M.S. 02-19  
Printed in United States