THIS IS ISSUED IN STRICT CONFIDENCE THAT IT IS NOT USED AS A BASIS FOR MANUFACTURE OR SALE AND THAT IT IS NOT COPIED, REPRINTED OR DISCLOSED TO A THIRD PARTY EITHER WHOLLY OR IN PART WITHOUT THE PRIOR WRITTEN CONSENT OF CAL TEST ELECTRONICS, INC.



99 Washington St. Melrose MA, 02176 1.800.517.8431 | 781.665.0780 (Fax)

REVISIONS			
REV.	DESCRIPTIONS	DATE	APPROVED
_	CLASS A RELEASED	7/12/04	

- 1. TEST PROBE LEAD w/4mm SPRING CONTACT TIP, 0.75mm2, SILICONE JACKETED WIRE.
- 2. SPECIFICATIONS:

WIRE:

DOUBLE INSULATED SILICONE (-60° C TO $+180^{\circ}$ C) 195x0.07mm STRANDED BARE COPPER, 0.75mm2 CROSS SECTION (18AWG), Ø.146±.008 (Ø3.7±0.2mm) O.D.

INSULATED HOUSINGS:

PA6 (NYLON) THERMOPLASTIC. UI 94V-0.

CONTACTS:

PLUG BODY & TIP: BRASS, NICKEL PLATED

CONTACTS: 4mm, 9 LEAF-BECU, NICKEL PLATED.

INSULATED TIP ON PLUG BODY, GREY

3. RATING:

1,000V CATIII P2 PER IEC61010-031

CURRENT: 12A MAX.

TEMPERATURE: -20° C TO $+80^{\circ}$ C.

CE DECLARATION OF CONFORMITY:

VOLTAGE: 1000V CATIII P2, IEC61010-031 (HANDHELD)

CURRENT: 12A MAX.





