



PROMAX

CT-337

SMART CURRENT CLAMP METER

WITH AUTOMATIC MEASUREMENT SELECTION

FEATURING IMPEDANCE AND CAPACITANCE MEASUREMENT, DIODE TEST, CONTINUITY TEST AND FREQUENCY MEASUREMENT

The measures included in the **CT-337** current clamp are designed for the day to day of the electrician installer. It is possible to work in direct (DC) and alternating (AC) current installations, and to measure electronic components.

The **automatic measurement type selection** prevents mistakes that may damage the instrument when configuring the ranges. This makes the clamp very adequate to be used in vocational training.

The **CT-337** clamp can toggle automatically between voltage and current DC/AC automatically adjusting the measurement range; it also has smart auto-selection of the electronic component under test (impedances, capacitors, diodes).

MEASUREMENTS INCLUDED IN THE CT-337 CURRENT CLAMP

- ✓ **DC/AC voltage:** Up to 1000 V
- ✓ **DC/AC current:** Up to 1000 A
- ✓ **Continuity test:** Audible tone
- ✓ **Diode test:** Audible tone
- ✓ **Impedance:** Up to 60 MΩ
- ✓ **Frequency:** Up to 1 kHz
- ✓ **Capacitance:** Up to 600 µF

SPECIFICATIONS

- ✓ **Display:** Backlit LCD screen
- ✓ **Polarity:** Automatic, on-screen indication
- ✓ **Smart selection of measurement type and range**
- ✓ **Dimensions:** 94 (W.) x 241 (H.) x 46 (D.) mm
- ✓ **Functions:** HOLD, MAX HOLD, MIN HOLD
- ✓ **OVERRANGE:** Built-in overrange protection
- ✓ **Power supply:** 9 V LR61 battery





CT-337 CURRENT CLAMP 1000 V, 1000 A

SPECIFICATIONS	CT-337 SMART CURRENT CLAMP 1000 V, 1000 A
Display	Backlighted LCD screen
Display functions	HOLD, MAX HOLD, MIN HOLD
Polarity	Automatic: Positive by default and on-screen negative polarity indication
OVERRANGE	Built-in overrange protection for Vdc/VAC, Adc/Aac, Capacitance, Frequency and Impedance measurements
Analogue to Digital Conversor	6000 counts
Protection class	IEC1010 CAT III 1000 V
Max conductor diameter	32 mm
Smart measurement selection	Automatic measurement selection for DC/AC Voltage with auto range and for DC/AC Current. Automatic measurement and range selection for Impedance, Diodes, Continuity or Capacitance.
DC voltage	
Scales	600mV / 6V / 60V / 600V / 1000V
Resolution	0.1 mV / 0.001V / 0.01V / 0.1V / 1V
Accuracy	600 mV scale: $\pm(0.8\% \text{ rdg.} + 2 \text{ digits})$ / Other scales: $\pm(0.8\% + 1 \text{ digit})$
Input impedance	10 M Ω
Overload protection	600 mV scale: $\pm 500 \text{ V}$ / Other scales: $\pm 1000 \text{ V}$
AC voltage	
Scales	6V / 60V / 600V / 1000V
Resolution	0.001V / 0.01V / 0.1V / 1V
Accuracy	$\pm(1\% \text{ rdg.} + 2 \text{ digits})$
Input impedance	10 M Ω
Overload protection	1000 V
DC/AC current	
Scales	600A / 1000A
Resolution	0.1A / 1A
Accuracy	600 A scale: $\pm(1.5\% \text{ rdg.} + 15 \text{ digits})$ / Scale 1000 A: $\pm(2\% + 8 \text{ digits})$
Overload protection	1000 A
Diode test	Short/open circuit, pass/fail test
Continuity test	Audible tone when the impedance value is below 20 Ω
Capacitance	
Scales	6nF / 60nF / 600nF / 6 μ F / 60 μ F / 600 μ F
Resolution	0.001nF / 0.01nF / 0.1nF / 0.001 μ F / 0.01 μ F / 0.1 μ F
Accuracy	$\pm(3\% \text{ rdg.} + 5 \text{ digits})$
Frequency	From 40 Hz to 1kHz (resolution 0.001 kHz). Accuracy $\pm(0.5\% \text{ rdg.} + 2 \text{ digits})$
Impedance	
Scales	600 Ω / 6k Ω / 60k Ω / 600k Ω / 6M Ω / 60M Ω
Resolution	0.1 Ω / 0.001k Ω / 0.01k Ω / 0.1k Ω / 0.001M Ω / 0.01M Ω
Accuracy	600 Ω scale: $\pm(1\% \text{ rdg.} + 2 \text{ digits})$ / Other scales: $\pm(1.5\% \text{ rdg.} + 2 \text{ digits})$
Overload protection	$\pm 350 \text{ Vdc}, 350 \text{ VAC}$
Power supply	9 V LR61 battery
Mechanical features	94 (W.) x 241 (H.) x 46 (D.) mm / 429 g, including battery
Included accessories	Test leads, Carrying pouch

DESIGN AND SPECIFICATIONS ARE SUBJECT TO CHANGES WITHOUT PRIOR NOTICE 03-23

