



Melrose, MA 02176 Phone 781-665-1400 Toll Free 1-800-517-8431

# Measuring Quality

# DEG-2000 Electric Gauge Display with 2 Channel Input

The Series DEG-2000 electric gauge micrometer display is a precision, dimensional measuring instrument when combined with an electronic probe sensor. Electric micrometer gauging is a non-destructive testing method that utilizes a contact electronic LVDT sensor input.

The DEG-2000 micrometer display with separate, customized probe sensors performs fast, easy and precise dimensional analysis on components. Pass/Fail feedback is instant with the integral easy view three-color LED bar-graph display. All DEG-2000's come standard with RS-232 serial communications for data analysis on PC's. An Excel spreadsheet program is available for download for free from the Shimpo website that allows communication and data storage for further analysis.

The DEG-2000 offers sufficient magnification and reliability to measure small tolerances down to 0.1 micron. Due to its fast response, outstanding tolerance and accurate repeatability, Tosok gauge micrometers are ideal for quality measurements on the production floor or in the lab.



#### **Features**

- Red/Orange/Green 3-color, display with programmable set points makes it easy to quickly view measurements and make go/no-go judgments
- Actual values presented on the 8-digit alphanumeric display
- In coordination with the max./min. masters and the sensors, control keys are used to automatically calibrate the zero and full scale of the display
- Compact size allows placement on any bench.
- Utilizing the standard serial output communications, data can be downloaded to a PC for processing and further evaluation
- Several options are available such as judgment result output, rank output, BCD output and Digimatic output.
- Mathematical calculations can be set to automatically calculate between two inputs for instant determination of distance comparison between dimensions.

#### NIDEC-SHIMPO CORPORATION

#### **DEG-2000 Specifications**

Input	2 Electric Channels	
Measuring Range µm (mm)	20 (0.02), 100 (0.1), 1000 (1)	
Resolution in $\mu$ m (mm)	0.1 (0.0001), 0.1 (0.0001), 1 (0.001)	
Display	3 color with Green (OK), Red (No Go) Measurement Values: 8 digits plus decimal point	
Auto Mastering Range	Zero position: ±30% (full scale) Sensitivity: ±20% (full scale)	
Power Requirement	85 to 264 VAC, 50/60 Hz 100-VAC	
Power Supply Capacity	30 VA	
Operating Temperature	32 to 113°F (0 to 45°C)	
Dimensions	4.7" wide x 7" deep x 6" height (120 × 180 × 150 mm)	
Weight	6 lb (2.7 kg)	
Warranty	1 year	

## **Ordering Details**

DEG-2000-2
------------

## **Options**

-DP	Digimatic Output
-DR	Rank Output
-BC	BCD Output

#### **Optional Accessories**

CAG2000-OP-CB-1 RS-232 Communication 9 pin for PC	ation Cable
---	-------------



Customized Electric LVDT Sensor ordered separately.