



# 400A Dual Display Clamp Meter w/ Test Lead Storage



## Functions

- 400A AC
- 1000V DC
- 750V AC
- 40 kΩ Resistance
- DC mV
- Audible Continuity
- Diode Test
- Non-Contact Voltage Detection

## Features

- Dual Display
- Test Lead Storage
- Min/Max/Hold
- High-voltage alert
- Easy access battery cover latches
- Raised molding
- Auto ranging
- Auto Off
- Low battery indicator
- 1-Year limited warranty

## Application

- Measure voltage, circuit continuity, resistance, and diode malfunctions. Check system boards and live wires.

## Includes

- Test Leads (ATL55)
- Alligator Clips (AAC3)
- Batteries, 2 (AAA)
- Zippered Pouch
- Manual



DESIGNED BY  
MADE BY  
**Uei**

Safety Rated: CATIV 300V / CATIII 600V  
Certified by ETL to IEC 61010-1, 3rd edition



## Specifications

### AC Amps Measurement

Range	Resolution	Accuracy	Overload Protection
60.00A	0.01A	±2.9% + 15dgts	600V RMS
600.0A	0.1A	±1.9% + 8dgts	

45Hz to 400Hz Averaging RMS  
 Minimum Current for Clamp Measurement: 0.3A

### DC Volts Measurement

Range	Resolution	Accuracy	Overload Protection
400.0mV	0.1mV	±0.5% + 5dgts	1000V RMS
400.0V	0.1V	±0.5% + 5dgts	
1000V	1V	±0.8% + 10dgts	

### AC Volts Measurement

Range	Resolution	Accuracy	Overload Protection
400.0V	0.1V	±2.0% + 5dgts	750V RMS
750V	1V		

45Hz to 400Hz Averaging RMS

### Ohms Measurement

Range	Resolution	Accuracy	Overload Protection
4.000kΩ	0.001kΩ	±1.0% + 4dgts	600V RMS
40.00kΩ	0.01kΩ		

### Diode Test

Range	Open Circuit Voltage	Test Current(Typical)	Overload Protection
4.0V	< 3.0V DC	0.25mA	600V RMS

### Audible Continuity Measurement

Open circuit voltage: < 0.44V	Overload Protection
Threshold Approx : < 40Ω	600V RMS

Safety Rated: CATIV 300V / CATIII 600V  
 Certified by ETL to IEC 61010-1, 3rd edition

### Downloads



Manual



Data Sheet



0 53533 50928 1

Made in KOREA