EasyView[™] Dual Input Thermometers Choice of Basic Type K or Datalogger model compatible with 7 Types of Thermocouples

Common Features:

- Compact and rugged design features large backlit display
- Displays [T1 plus T2] or [T1-T2 plus T1] or [T1-T2 plus T2]
- Selectable units of °F, °C, K (Kelvin)
- Wide temperature range with 0.1°/1° resolution
- · Timer function displays elapsed time plus the time when MIN and MAX readings are taken
- OFFSET key used for zero function to make relative measurements
- · Data Hold function freezes reading on display
- Auto Power off to save battery life
- · Low battery and overrange indication
- · Records Max/Min readings for later recall
- Complete with built-in stand, protective holster, two Type K bead wire temperature probes, and 6 AAA batteries



Features:

• Basic Type K Dual input

Additional Features:

- Dual input accepts Types J, K, E, T, R, S, and N thermocouples
- Built-in datalogger stores up to 8800 data sets
- RS-232 port to transfer data to PC for analysis
- Real Time Clock
- Includes Windows® 95/98/NT/2000/ME/XP compatible software and cable

Œ

Specifications:		
Thermocouple Type	EA10	EA15
J:	_	-200 to 1994°F
		-150 to 1090°C
_K:	-200 to 1999°F (-200 to 1360°C)	-200 to 1999.9°F (-150 to 1370°C)
T:	_	-200 to 752°F (-150 to 400°C)
E:	_	-200 to 1598°F (-150 to 870°C)
R:	_	35 to 1999.9°F (2 to 1767°C)
S:	_	35 to 1999.9°F (2 to 1767°C)
N:	_	-200 to 1999.9°F (-150 to 1300°C)
Resolution:	0.1°	0.1°
Basic Accuracy:	±0.3% (+2°F/+1°C)	±0.05% rdg (+0.6°F/+0.3°C) Types J,K, E, T, N
		±0.05% rdg (+4°F/+2°C) Types R, S
Dimensions:	6x2.8x1.5" (152x72x37mm)	6x2.8x1.5" (152x72x37mm)
Weight:	8.3oz (235g)	8.3oz (235g)

Ordering Information:

EA10EasyView™ Dual K Thermometer
EA10-NIST ...EasyView™ Dual K Thermometer with NIST Certificate
EA15EasyView™ Temperature Datalogger
EA15-NIST ...EasyView™ Temperature Datalogger w/ NIST Certificate 871515Type K General Purpose Temperature probe 872501-SBead wire temperature probe 409996Soft Vinyl Pouch Carrying Case

