

EasyView™ Type K Single Input Thermometer

View at www.TestEquipmentDepot.com

Large dual LCD display and Memory function

Simultaneously displays current temperature and Max, Min, or Avg readings.
Manually store and recall up to 150 readings for further analysis.

Features:

- Compact and rugged design with high contrast large LCD display
- Manually store/recall up to 150 readings
- Wide temperature range with 0.1°/1° resolution
- Data Hold function freezes reading on display
- Records Max/Min/Avg readings for later recall
- Offset key used for zero function to make relative measurements
- Auto Power off with disable feature
- Low battery and overrange indication
- Complete with built-in stand, protective holster, Type K bead wire temperature probe (-4 to 482°F/-20 to 250°C) and 6 AAA batteries



Optional Accessories:

Model TP875 — Optional Type K Bead Wire Temperature Probe measures from -58 to 1000°F (-50 to 538°C) with subminiature connector. Includes a banana adaptor connector for use with meters with banana adaptor inputs.

Model TP200 — Optional Type K Pipe Clamp Temperature Probe for hands-free superheat/sub-cooling temperature measurement from -4°F to 200°F (-20°C to 93°C)

Visit www.extech.com for a wide selection of Temperature Probes including Penetration and Surface Probes.

Specifications	
Temperature (Type K)	-58 to 1999°F (-50 to 1300°C)
Basic Accuracy	0.3% rdg
Resolution	0.1°/1°
Memory	Manual store/recall up to 150 readings
Dimensions	5.9 x 2.8 x 1.3" (150 x 72 x 35mm)
Weight	8.3oz (235g)

Ordering Information:

- EA11AEasyView™ Type K Single Input Thermometer
 EA11A-NIST ..EasyView™ Type K Single Input Thermometer w/ NIST Cert.
 TP870Type K Bead Wire Temperature Probe (482°F/250°C)
 TP875Type K Bead Wire Temperature Probe (1000°F/538°C)
 TP200Type K Pipe Clamp Probe (200°F/93°C)
 409996Soft Vinyl Pouch Carrying case.

Test Equipment Depot - 800.517.8431 - 99 Washington Street Melrose, MA 02176

FAX 781.665.0780 - TestEquipmentDepot.com

Specifications subject to change without notice.

Copyright © 2007-2008 Extech Instruments Corporation. All rights reserved including the right of reproduction in whole or in part in any form.

