99 Washington Street Melrose, MA 02176 Phone 781-665-1400 Toll Free 1-800-517-8431

pH600/CD600/CD601/CD610/CD611/CD97

pH/EC & TDS Economical Pocket Testers

Milwaukee's economical testers are easy-to-use and low cost instruments to measure quick and reliable pH, EC or

Measuring electrical conductivity is the best way of checking the amount of salt or dissolved solids (TDS) in water. Milwaukee provides you with a range of pocket testers that will allow you to measure from very low to very high conductivity solutions.

All EC/TDS testers compensate for the temperature variance automatically.



Specifications	pH 600 📗 🔰	CD 600	CD 601
	pH600	CD600	CD601
Range	0.0 to 14.0 pH	0 to 1990 ppm	0 to 1990 μS/cm
Resolution	0.1 pH	10 ppm	10 μS/cm
Accuracy	±0.1 pH	±2% full scale	±2% full scale
Calibration	manual, 1 point		Name of the last
Temperature Compensation		automatic from 5 to 50°C	automatic from 5 to 50°C
Environment	0 to 50°C / 32 to 122°F; max RH 95%	0 to 50°C / 32 to 122°F; max RH 95%	0 to 50°C / 32 to 122°F; max RH 95%
Battery Type / Battery Life	3 x 1.5V, alkaline / 700 hours of use	4 x 1.5V, alkaline / 350 hours of use	4 x 1.5V, alkaline / 350 hours of use
Dimensions / Weight	150 x 30 x 24 mm / 85 g	150 x 30 x 24 mm / 85 g	150 x 30 x 24 mm / 85 g

Specifications	CD 610	CD 611	CD 97
	CD610	CD611	CD97
Range	0 to 10000 ppm	0 to 20000 μS/cm	0 to 1000 ppm
Resolution	100 ppm	100 μS/cm	1 ppm
Accuracy	±2% full scale	±2% full scale	±10 ppm
Temperature Compensation	automatic from 5 to 50°C	automatic from 5 to 50°C	automatic from 5 to 50°C
Environment	0 to 50°C / 32 to 122°F; max RH 95%	0 to 50°C / 32 to 122°F; max RH 95%	0 to 50°C / 32 to 122°F; max RH 95%
Battery Type / Battery Life	4 x 1.5V, alkaline / 350 hours of use	4 x 1.5V, alkaline / 350 hours of use	4 x 1.5V, alkaline / 350 hours of use
Dimensions / Weight	150 x 30 x 24 mm / 85 g	150 x 30 x 24 mm / 85 g	150 x 30 x 24 mm / 85 g

Accessories

M10004B pH 4.01 buffer solution 20 mL

sachet (25 pcs)

M10007B pH 7.01 buffer solution 20 mL sachet (25 pcs)

M10010B pH 10.01 buffer solution, 20 mL

sachet (25 pcs) M10030B

12880 µS/cm calibration solution, 20 mL (25 pcs)

M10031B 1413 μS/cm calibration solution, 20 mL (25 pcs)

M10032B 1382 ppm (mg/L) calibration solution, 20 mL (25 pcs)

M10038B 6.44 ppt (g/L) calibration solution,

20 mL (25 pcs)

M10080B 800 ppm calibration solution

20 mL (25 pcs)

MA9015 Electrode storage solution, 230 mL MA9016 Electrode cleaning solution, 230 mL M10000B Electrode rinse solution, 20 mL

(25 pcs)

Ordering Information

pH600, CD600, CD601, CD610, CD611 and CD97 are supplied complete with protective cap, calibration screwdriver, batteries and instructions.

