

5 Commonwealth Ave Woburn, MA 01801 Phone 781-665-1400 Toll Free 1-800-517-8431



Wireless High Accuracy Indoor Air Quality Monitor

Your data, anytime, anywhere

- Monitors Indoor Air Quality (IAQ)
- Measures:
 - Temperature
 - Humidity
 - VOC's
 - PM1, PM2.5 and PM10
 - CO,
 - Pressure
- Automatically uploads data to the EasyLog Cloud
- Coloured status ring shows IAQ level
- Sounder and instant notifications when IAQ is poor
- Detects VOCs from paints, lacquers, paint strippers, cleaning products, furnishings, glues, adhesives and alcohol
- Power supply included
- Internal back-up battery if power interrupted



The EL-WEM+ continually monitors Indoor Air Quality, with a coloured status ring to display the IAQ level at a glance. It also automatically uploads data to the EasyLog Cloud, allowing your complete set of data measurements to be viewed,

analysed and downloaded from any

internet-enabled device.

The IAQ level is rated in five levels from Excellent to Inadequate, and if it falls to Poor the sounder is activated and email and SMS notifications can be sent

to your selected contacts. There is also a configurable night mode, which mutes the sounder and turns the LEDs on.

The EL-WEM+ is simple to set up, with a single button press and the EasyLog Cloud App.

A power supply is included and the unit also has an internal back-up battery, allowing it to continue operating in low power mode if mains power is temporarily lost.



The status ring indicates the current IAQ level at a glance





EL-WEM+





Your data, anytime, anywhere

IAQ RATING INDEX

Indoor Air Quality is rated as one of five levels, ranging from Excellent down to Inadequate. This rating uses a points based system, taking measurements from five parameters. The points from each parameter are added together to give the final IAQ rating:

Parameter	Excellent 5 points	Good 4 points	Fair 3 points	Poor 2 points	Inadequate 1 point
Temperature °C	18 € T €21	17 < T < 18 21 < T ≤ 22	16 €T < 17 22 < T ≤ 23	15 ≤ T < 16 23 < T ≤ 24	T < 15 T > 24
Relative Humidity %	40 ≤ RH ≤ 60	30 ≤ RH < 40 60 < RH ≤ 70	20 < RH < 30 70 < RH < 80	10 ≤ RH < 20 80 < RH ≤ 90	RH < 10 RH > 90
TVOC (index)	TVOC < 50	51 ≤ TVOC < 100	101 ≤ TVOC < 150	151 ≤ TVOC < 200	TVOC ≥ 201
PM10 μg/m³	PM < 33	33 ≤ PM < 58	58 ≤ PM < 75	75 ≤ PM < 91	PM ≽ 91
CO ² ppm	CO ² < 600	600 ≤CO² < 800	800 ≤ CO ² < 1500	1500 ≤ CO ² < 1800	CO ² ≥ 1800
IAQ Rating	≥ 23 points	≥ 20 points	≥ 15 points	≥ 10 points	< 10 points





Plug in the power supply, then press the central button to turn the device on.

Download and login to the EasyLog Cloud App on your mobile device. Select "Setup Device" and follow the onscreen instructions to add your EL-WEM+.

You can now view the EL-WEM+'s data and change settings either in the EasyLog Cloud App or by visiting your account at: www.easylogcloud.com







Your data, anytime, anywhere

EasyLog Cloud Your Data: Anytime. Anywhere.



Easily access your most important data, anywhere



Automatic emails alerts and SMS





Connect data loggers from multiple sites in one account



Remotely manage all of your data logger devices



Graph, review and analyse your data



Audits are easy with our event log system



Secure Cloud storage



Configurable user profiles

EasyLog Cloud App

Available for Android and Apple devices, the EasyLog Cloud app enables you to monitor and manage your wireless sensors on the go.





Access your vital data from any internetenabled computer, tablet or mobile device with EasyLog Cloud. From single locations to worldwide operations, the system is perfectly scalable and can run through your existing wireless networks.

Critical events are notified to specific users in seconds via an alarm system that's easily tailored to your exact requirements.

Data is accessible 24/7 and powerful online tools make it simpler than ever to view, compare and analyse readings. An audit trail is automatically created that includes both system and data events.

Starter and Professional accounts are available, always flexible and with no locked-in contracts.





Your data, anytime, anywhere

INCLUDED IN THE BOX







PSU Power supply



3 x ADAPTORS




CABLE **Power cable**

ALSO IN THE RANGE



EL-WEM

DIMENSIONS



Visit lascarelectronics.com/data-loggers to see our full range of data loggers and measuring devices

SPECIFICATIONS







EL-WEM+

-								
16	Υi	n	1	ai	F	7	П	7
III.	Ш	ш	ы	듸	ш	3	3.1	JL:

-20 to +60°C Measurement Range

±0.6°C at 15°C Measurement Accuracy

Humidity

0 to 95%RH Measurement Range

±3% Measurement Accuracy

Volatile Organic Compounds (VOC)

Biogenic VOC Accuracy ±5%

Particulate Matter (PM)

Particle Size Measured PM10, PM2.5 and PM1

0 to $1000 \mu g/m^3$ Measurement Range

Carbon Dioxide (CO₂)

0 to 40,000ppm Measurement Range

Measurement Accuracy ±3%

Pressure

300 to 1100mbar Measurement Range

±0.6mbar Measurement Accuracy

Dimensions

Height x Diameter 170.5 x 77mm



