



Convenient Pressure Testing with an Easy-to Read Display, Built-in Magnet and Intuitive Interface



99 Washington Street
Melrose, MA 02176
Phone 781-665-1400
Toll Free 1-800-517-8431

Visit us at www.TestEquipmentDepot.com

Functions

- Range of -60 to +60 inH₂O
- Differential pressure

Features

- Dual input differential measurement to ± 60 inches of water column
- Measures in 11 scales; inH₂O, psi, bar, mBar, kPa, inHG, mmHG, ozin, FtH₂O, cmH₂O and kgcm.
- Magnetic mount
- Auto ranging
- Backlit display
- Data hold
- Min/Max
- Zero button
- 1-Year limited warranty

Applications

- Validate pressures in accordance with equipment manufacturer's specification for optimal system efficiency and safety.
- Measure draft, gas supply, manifold or burner pressures
- Dual input offers users the ability to measure pressure drops across heat exchangers, cooling coils, supply and return registers and filters





Includes

- Flexible transparent silicone tubing
(2) 18" length 1/4" diameter
- Barbed gas valve fitting (2)
- Soft pouch (7.48" x 4.33" x 1.96")
- Manual
- Battery

Specifications

Unit of Measure	Range	Resolution	Accuracy (77 °F)
bar	± 0.200	0.001	± 0.3% Full Scale Output
Ounces/Sq. Inch	± 46.60	0.01	
psi	± 2.900	0.001	
inHg	± 5.904	0.001	
mBar	± 200.0	0.1	
mmHg	± 150.0	0.1	
kPa	± 20.00	0.01	
Kg/Sq. cm	± 0.204	0.001	
InH ₂ O	± 60	0.01	
FtH ₂ O	± 6.689	0.001	
cmH ₂ O	± 203.9	0.1	