

Visit us at www.TestEquipmentDepot.c

Simultaneous real-time display of HCHO/CH2O (Formaldehyde) and TVOC (Total Volatile Organic Compounds) concentrations in the air

## Features:

- Two selectable units of measure (ppm, mg/m<sup>3</sup>)
- Fuel Cell Formaldehyde Sensor Technology for high accuracy measurement
- Backlit dual LCD
- Audible and visual high/low alarms for HCHO
- Auto power off conserves battery life
- Includes rechargeable 7.4V Li-Po battery and AC charger/adapter

## **Applications:**

Potential sources for TVOCs include paints, finishes, adhesives, cigarette smoke, pesticides, personal care products, car exhaust, new furnishings, wall coverings, household cleaners, and cooking fuels. Chemicals include: Acetone, Ethylene Glycol, Formaldehyde, Xylene, 1,3-butadiene, Tetrachloroethene, Hydrogen Sulfide, Ammonia, Toluene, Benzene, Methylene Chloride, Perchloroethylene and MTBE.



## **Specifications**

- <b>-</b>	
Formaldehyde (HCHO/CH2O) Range	0.00 to 5.00 mg/m <sup>3</sup> (ppm)
Accuracy	±5% FS
Resolution	0.01 mg/m <sup>3</sup> (ppm)
TVOC Range	0.00 to 9.99 mg/m <sup>3</sup> (ppm)
Accuracy	±5% FS
Resolution	0.01 mg/m <sup>3</sup> (ppm)
Response Time	$\leq$ 2 seconds
Power	Rechargeable 7.4V Li-Po Battery
Dimensions	6.5 x 2.4 x 1" (165 x 60 x 25mm)
Weight	20.6oz (584g)

Ordering Information:

FM260

Formaldehyde and TVOC Meter





## Test Equipment Depot - 800.517.8431 - 5 Commonwealth Ave, MA 01801 TestEquipmentDepot.com