



Food TempTestr® II Infrared Thermometer

Easy way to determine safe food preparation or storage temperatures

- Noncontact measurement eliminates the risk of cross-contamination** – Ideal for food inspections and HACCP programs where harmful bacteria grows most rapidly
- Scan numerous surfaces quickly and easily** – Safe, noncontact readings in only ½ second
- LEDs quickly indicate if food temperatures are in the bacterial growth safety** – Green LED light indicates food-safe hot and cold holding temperatures. Red LED light indicates that food is within the food temperature danger zone.
- Sealed, hand-washable IP54 housing**
- Compact design allows for easy one-handed operation**
- Includes one 9 V battery and wrist strap**



Specifications & Ordering Information



Catalog number	WD-35625-45
Range	-30 to 200°C (-20 to 400°F)
Accuracy	±1°C (±2°F) from 0 to 65°C (32 to 150°F)
Response time	0.5 second
Emissivity	Preset at 0.97
Laser sighting	LED (non-laser)
Distance-to-target ratio	2.5:1
Power	One 9 V battery (included)
Dimensions	2"L x 1¼"W x 6"H (5.1 x 3.2 x 15.2 cm)

Food Safety Infrared Thermometer

Check critical food temperatures and monitor HACCP food safety zones with this combination contact/noncontact thermometer

- Go/no-go LEDs provide quick noncontact surfaces checks of HACCP bacterial growth safety zone** – Green lights indicate safe temperatures below 4°C (40°F) and above 60°C (140°F). Red light indicates the HACCP danger zone between 4 to 60°C (40 to 140°F).
- Target illumination** – Indicates target measurement area at working distances of 2 to 12" (5.1 to 30.5 cm)
- Swing-out contact penetration probe** – For internal temperature checks, folds in for storage
- Built-in countdown timer with alarm** – Monitor cooking and cooling intervals and HACCP exposure times—set countdown timer to a maximum of eight hours
- Sealed, hand-washable IP54 housing**
- Includes one 9 V battery, carrying case, and quick reference card**



Target illumination clearly indicates target area.



Contact penetration probe swings out for fast temperature checks.

Specifications & Ordering Information



Catalog number	WD-35625-40	
Mode	Infrared	Contact
Range	-35 to 275°C (30 to 525°F)	-40 to 200°C (-40 to 390°F)
Accuracy	±1°C (±2°F) from 0 to 65°C (32 to 150°F)	±0.5°C (±1°F) from 0 to 65°C (32 to 150°F)
Response time	500 msec	5 sec
Emissivity	Preset at 0.97	
Laser sighting	LED (non-laser)	
Distance-to-target-size ratio	2.5:1	
Power	One 9 V battery (included)	
Dimensions	Overall: 2"L x 1¼"W x 6½"H (5.1 x 3.2 x 16.5 cm); contact probe: 3¼"L x ¼" dia (8.3 x 0.3 cm)	

WD-35625-70 Replacement probe for thermometer 35625-40
WD-86106-10 Antimicrobial sanitizing wipes. Box of 100