

GAS PRESSURE KITS

Please read this manual carefully and thoroughly before using this product.

Get accurate pressure readings when checking and setting manifold pressure of furnaces and appliances that use natural gas or LP gas

OPERATING INSTRUCTIONS:

- 1. Turn off gas. Remove gas inlet supply/ manifold fitting.
- 2. Use hose clamp to attach non-flared end of tubing to gauge
- 3. Install supplied brass fitting into manifold
- 4. Push flared end of tubing onto barbed end of brass fitting. Turn on gas and begin pressure test.
- 5. Remove hose
- 6. Reassemble manifold

NOTE: Before taking final pressure reading, tap gauge lightly to relieve any built-up friction

CAUTION!

Handle carefully. The special diaphragm gauge is very sensitive. Do not drop! Do not over pressurize!

APPLICATIONS:

- Home
- Office
- Factory

FEATURES:

- Measure natural gas (methane) or LP gas pressure across appliance manifolds
- Test gas stoves, furnaces, dryers and other gas appliances. Can also be used for other corrosive gases.
- Large 2.5 in. diameter diaphragm gauge is calibrated in inches of water column, also shows ounces per square inch (GPK015/GPK035 only)
- Magnified lens
- Easier to use than a manometer
- **GPK005** is calibrated in psi and meets requirements of Section 406.4 of the NEW YORK CITY FUEL GAS CODE (2008)

SPECIFICATIONS:

- GPK005 Range: 0 to 5 psi
- GPK015 Range: 0 to 15 inches of water column (in. H₂O)/0 to 9 ounces per square inch (oz./in²)
- **GPK035** Range: 0 to 35 inches of water column (in. H₂O)/0 to 20 ounces per square inch (oz./in²)
- Measurement Accuracy (all models): ±1.5% of full-scale range
- Dimensions: 2.5 in. gauge, 39 in. rubber tubing
- Weight: 10.2 oz. (285g)

INCLUDES:

2.5 in. diameter diaphragm gauge, 39 in. of rubber tubing, 3/8 in. NPT brass fitting for quick connection to appliance manifold, hose clamp, molded hard case



- Appliances
- Piping
- Recreational Vehicles