

Benchmark® Hotplates, Stirrers & Hotplate Stirrers



- Large, white ceramic top plate
- Compact, 8 x 10" footprint
- Three models:
Hotplate, Stirrer and Hotplate Stirrer

The Benchmark hotplates, stirrers and hotplate-stirrers feature an exceptionally durable, chemical resistant white ceramic work surface. Their space-efficient design (8 X 9 in. footprint), makes them ideal for use on crowded benches and inside of bio-hoods.

Advanced microprocessor controls with convenient turn knobs allow quick, precise adjustment and maintenance of speed and temperature. Safety Indicator LED's on the front panel indicate when the heating and/or stirring functions have been activated.

With a square 7.1 in work surface, all three models are compatible with a wide variety of popular sizes of borosilicate glass beakers, flasks, bottles and other vessels. The hotplate/magnetic stirrer model (H4000-HS) comes complete with a support rod for mounting thermometers and temperature probes.

Technical Data

Hotplate (H4000-H)

Temperature Range:	80°C to 380 °C*
Platform:	7.1 x 7.1 in./ 18 x 18 cm
Control:	Quick adjustment knob
Dimensions:	8 (W) x 10 (D) x 4.5 (H) in.
Electrical Data:	120V, 60 Hz / 230V, 50/60 Hz

Magnetic Stirrer (H4000-S)

Speed Range:	60 to 1500 rpm
Platform:	7.1 x 7.1 in./ 18 x 18 cm
Control:	Quick adjustment knob
Dimensions:	8 (W) x 10 (D) x 4.5 (H) in.
Electrical Data:	120V, 60 Hz / 230V, 50 Hz

Hotplate Stirrer (H4000-HS)

Temperature Range:	Amb. 80°C to 380 °C*
Speed Range:	60 to 1500 rpm
Platform:	7.1 x 7.1 in./ 18 x 18 cm
Control:	Quick adjustment knob
Dimensions:	8 (W) x 10 (D) x 4.5 (H) in.
Electrical Data:	120V, 60 Hz / 230V, 50 Hz

Ordering Information

H4000-H	Benchmark hotplate, 115V*
H4000-S	Benchmark magnetic stirrer, 115V*
H4000-HS	Benchmark hotplate magnetic stirrer, 115V*

* To order a product in 230V, please add -E to item number.

