HDV700 Series High-Performance Videoscope



section on next page)

The HDV700 is a versatile and lightweight professional videoscope that is designed for inspections in locations that are difficult or unsafe to access. With one or more of the eight waterproof (IP67) camera probes*, you can use the HDV700 for condition monitoring in manufacturing, HVAC/R, plumbing, building, and automotive applications. A range of small diameter and articulating camera probes are available to give you clear visibility of components from the 5-inch color touchscreen display. Easily maneuver the narrow probes into small openings without disassembling equipment. The HDV700 also features multiple data recording options so you can easily create reports at the job site by transferring images and videos to your laptop.



HDV700 Series Features

- · View clear, bright images with a wide field-of-view on the 5-inch color capacitive touchscreen
- · Capture both still images and videos
- · Gain access to difficult-to-see components without disassembling equipment
- · Simultaneously view live camera image and a saved image side by side on the display to easily compare changes since last inspection
- · Record voice annotations and photo notes for advanced reports
- Efficiently manage your inspection data using the Session and Tag feature
- · Make it easy for a second person to inspect with you by connecting the display to a monitor using the HDMI video output

- · Inspect comfortably using the display stand and tripod mount
- Immerse the IP67-rated camera probes in water at a depth up to 1 m (3.2 ft) for 30 minutes max
- Each kit is complete with a HDV700 Videoscope Screen, camera probe (model dependent on kit ordered), 32 GB Micro SD card, USB-A to USB-C cable, HDMI Type A to Type D cable, Li-ion rechargeable battery (built-in), and universal adapter (with US, UK, EU, and AUS plugs)



HDV700 Videoscope Screen (No Camera Probes)		
Display (Resolution)	5" color TFT (800 × 480)	
Touchscreen (Backlight)	Capacitive touch (500 nits)	
Image/Video Format	JPEG (1280 × 720)/MP4 (1280 × 720)	
Voice and Text Annotation	Yes	
Video Output	Micro HDMI	
Data Communication Interface	USB-C, Micro SD	
Storage Capacity	Up to 64 GB micro SD (32 GB microSD included)	
Battery Type (Life)	Rechargeable 3.6 V Li-ion (5 hours)	

Tripod Mount	UNC 1/4"-20
Power	5 V, 3 A DC with universal adapters (US, EU, UK, AU)
Drop Test	1 m (3.28 ft)
IP Rating	Videoscope Screen: IP54 Camera probe: IP67
Dimensions [W × H × D]	161.9 mm × 127.9 mm × 30 mm (6.38 in × 5.04 in × 1.18 in)
Weight	705 g (1.55 lb)

HDV7	'00 Seri	ies Can	nera P	rohes

Model Number	Diameter	Length	Probe Flexibility	Resolution	Depth Of Field	Field of View	Direction of View
General Purpose							
HDV7C-55-HD-1	5.5 mm	1 m	O d-id	1280 × 720	- 10 mm to infinity	90°	Forward
HDV7C-55-3	5.5 mm	3 m	Semi-rigid	640 × 480			
Dual View Inspection							
HDV7C-49-DUAL-1	4.9 mm	1 m	Semi-rigid	1280 × 720	10 mm to infinity	90°	Forward & Side
2-Way 180°Articulatio	n Camera						
HDV7C-A2-39-HD-1	3.9 mm	1 m	Flexible, Stainless	1280 × 720	10 mm to infinity	90°	Forward
HDV7C-A2-45-15	4.5 mm	1.5 m	Steel Mesh	640 × 480			
4-Way 110°Articulatio	n Camera						
HDV7C-A4-60-1	6 mm	1 m	Flexible, Stainless	640 × 480	- 10 mm to infinity	87.1°	Forward
HDV7C-A4-60-3	6 mm	3 m	Steel Mesh	640 × 480			
Pipe Inspection							
HDV7C-P28-30	28 mm	30 m	Fiberglass	640 × 480	10 mm to infinity	150°	Forward


Ordering

Complete Kits

HDV710Vid	deoscope Kit with Semi-Rigid HD 5.5 mm × 1 m Camera Probe
HDV720Vid	deoscope Kit with Semi-Rigid Dual HD 4.9 mm × 1 m Camera Probe
HDV730Vio	deoscope Kit with HD Flexible 2-Way Articulating 3.9 mm × 1 m Camera Probe
HDV740Vio	deoscope Kit with Flexible 4-Way Articulating 6 mm × 1 m Camera Probe
HDV750Vic	deoscope Plumbing Kit with 28 mm Camera, 30 m Plumbing Spool and Probe Length Locator

Screen and Camera Probes (sold separately)





4-Way Articulation Range

