Test Equipment Depot - 800.517.8431 - 99 Washington Street Melrose, MA 02176 TestEquipmentDepot.com

exceeding 250 VAC.









The Heel Grounder HGC1M-EC delivers cost-effective compliance for highvolume grounder use. It consists of a re-positionable, two-layer sole with a 18-inch multi-strand ribbon, which helps increase it's durability.

| Specifications | Typical Value | Test Method |
|----------------|------------------------------|---------------------|
| Hook and Loop | 3/4" | |
| Sole Interior | Non-marking | |
| Sole Exterior | < 1 x 10 ⁶ ohms | |
| Total Grounder | < 1.0 x 10 ⁶ ohms | ESD-SP9.2, ESD TR53 |

| Item | Description |
|----------|--|
| HGC1M-EC | Economy Heel Grounder, 1 Megohm Resistor |

Note: This product is not recommended for use on equipment with operating voltage

CAUTION: The ESD Series is for electrostatic control. It will not reduce or increase your risk of receiving electric shock when using or working on electrical equipment. Follow the same precautions you would use without wrist straps, including:

- Make certain that equipment having a grounding type plug is properly grounded.
- Make certain that you are not in contact with grounded objects other than through the ESD Series.



2-layer Rubber Sole

Unless otherwise noted, tolerance ± 10%

Specifications and procedures subject to change without notice.



| HGC1M-EC ECONOMY HEEL GROUNDER | |
|--------------------------------|--|
| | |

DRAWING DATE NUMBER September HGC1M-EC 2015